Submittal Sheet

FG Series

Inline Centrifugal Fans



STANDARD FEATURES

- 100% Leak free
- Powered by external rotor motorized impeller
- Built-in thermal overload protection
- Speed controllable
- Can be installed in any positions and outdoor
- Mouting bracket and hardware included
- Five-year factory warranty

Model	A	C	D	E	F	Metal Gauge	Weight	ENERGY Star®	[®] 2100
FG 4	4	8 ¹ / ₂	6 ¹ / ₂	1	1	22	7	•	CERTIFIED
FG 4XL	4	9 ³ / ₄	6 ¹⁵ / ₁₆	1	1	22	8		
FG 5	5	8 ⁵ / ₈	6 ¹ / ₂	1	1	22	7	•	
FG 5XL	5	9 ³ / ₄	6	1 ¹ / ₈	1 ¹ / ₈	22	8		
FG 6	6	11 ³ / ₈	6 ¹ / ₄	1	⁷ / ₈	22	10	•	amca
FG 6M / FG 6XL	6	13 ¹ / _B	7	1	1	22	12		CERTIFIED RATINGS
FG 8	8	13 ¹ / ₄	6	1	1	22	12		
FG 8XL	8	13 ¹ / ₄	6	1 ¹ / ₈	1	22	13		
FG 10	10	13 ¹ / ₄	4 ³ / ₄	1 ¹ / ₈	1	22	12		AND COATROL ASSOCIATION INTERNATIONAL INC. [®]
FG 10XL	10	13 ¹ / ₄	4 ¹³ / ₁₆	1 1/4	1	22	14		
FG 12	12	16	6 ¹¹ / ₁₆	1 1/4	1	22	18		
FG 12XL	12	16	6 ¹¹ / ₁₆	1 ¹ / ₂	1	22	21		



Fantech Inc. certifies that the FG Series shown herein is licensed to beer the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

All dimensions in inches. Weights in pounds.

Line 1 2 3	Qty	Model No.	Tag	CFN	Л		SP		Fan RPM	Watts	Volts	Phase	Hert	2	Encl	
											Volts	Phase	Hertz		Encl	
3																
J																
Accessory Item	IS				1	2	3	4	Accessory Items				1	2	3	4
																_
Project:									Submitted:							
Customer: Location:									Approved:							

United States 10048 Industrial Blvd. • Lenexa, KS 66215 • 1.800.747.1762 • www.fantech.net Canada 50 Kanalflakt Way • Bouctouche, NB E4S 3M5 • 1.800.565.3548 • www.fantech.net



Fantech reserves the right to make technical changes. For updated documentation please refer to www.fantech.net