

QuietCool
ADVANCED WHOLE HOUSE FANS

QC STL PRO-5.5X Specifications

Air Flow	Hi: 5,044 CFM / Med: 4,238 CFM / Low: 2,870 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,750 CFM / Med: 3,070 CFM / Low: 2,010 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,681 SQFT to 2,522 SQFT
Energy Use	Hi: 490 Watts / Med: 268 Watts / Low: 88 Watts
Amps	Hi: 6.31 / Med: 3.67 / Low: 1.30
Motor Voltage	120 VAC, 60 Hz
# of Speeds	3
dBA	Hi: 50.7 / Med: 43.6 / Low: 35.6
Minimum Attic Clearance	38″
Duct Diameter	20″
Duct Length	9 feet
Motor Head Diameter	20 1/2″
Motor Head Length	13 1/2″
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16″ or 24″ on center
Minimum Suggested Attic Venting	6.73 SQ FT net free area
Ceiling Rough Opening	14 1/4″ x 30 1/4″
Removable Grille Outside Dimension	16″ x 32″
Shipping Weight	75 lbs.
Box Dimensions	39″ x 24″ x 39″
In The Box	-QC STL PRO-5.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM