
Air King Ventilation Products®

SPECIFICATIONS

BFQ70W

EXHAUST FANS

70 CFM/1.5 Sones @ 0.10" SP.
56 CFM @ 0.25" SP.



- **Grill**
  White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10¾" x 11⅝".

- **Blower Wheel**
  One piece polymeric wheel 5⅛" diameter, 2⅜" wide, with 48 fins.


- **Motor**
  Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

- **Fan Housing**
  PC/ABS polymeric, dimensions 8¾" x 9" x 3⅞".

- **Oval Duct Collar**
  Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation. Oval design accepts standard 4" round ducting and fits into standard 2" x 4" walls.

- **Ventilating Area**
  For bathrooms up to 70 sq. ft. For other rooms up to 85 sq. ft.

- **Single Pack Shipping Info**
  Box Dim: 11⅛" x 14" x 6¼"
  UPC: 0-8316294157-2
  Shipping Weight: 5¼ lbs.
  Available in contractor packs of 4 housings - model BFQ2HSG



Oval duct collar allows fan to be installed into walls using standard 2" x 4" studs.

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

- **Unit Mounting**
  Designed to mount in walls or ceilings with at least 4" of clearance. The unit is mounted directly to the joist or stud using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to ¾", with a rough-in opening of 8⅞" x 9⅛".

  Suitable for wall insert mounting when discharged vertically and mounted outside of shower enclosure

EXPANDED PERFORMANCE

	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	79	74	70	68	66	62	56	1.5	1300	22.3	0.3

PROJECT		ARCHITECT	
LOCATION		ENGINEER	
CONTRACTOR		SUBMITTED BY	DATE

FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS

U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 877-304-3785
Fax: (610) 696-8048

Canada:
Brampton, Ontario
Tel: 905-456-2033
Fax: (905) 456-1015

Specifications subject to change without notice.

Updated 5-22