QuietCool®
ADVANCED WHOLE HOUSE FANS

QC STL PRO-4.8X Specifications

Air Flow	Hi: 4,280 CFM / Med: 3,500 CFM / Low: 2,361 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,130 CFM / Med: 2,560 CFM / Low: 1,670 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,427 SQFT to 2,140 SQFT
Energy Use	Hi: 408 Watts / Med: 225 Watts / Low: 73.9 Watts
Amps	Hi: 5.16 / Med: 3.00 / Low: 1.07
Motor Voltage	120 VAC, 60 Hz
# of Speeds	3
dBA	Hi: 47.4 / Med: 41.6 / Low: 33.0
Minimum Attic Clearance	36″
Duct Diameter	18″
Duct Length	9 feet
Motor Head Diameter	18 1/2″
Motor Head Length	13 1/2″
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16″ or 24″ on center
Minimum Suggested Attic Venting	5.71 SQ FT net free area
Ceiling Rough Opening	14 1/4″ x 30 1/4″
Removable Grille Outside Dimension	16″ x 32″
Shipping Weight	75 lbs.
Box Dimensions	36″ x 22″ x 40″
In The Box	-QC STL PRO-4.8X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Controls

For more information, visit our website at:
QUIETCOOLSYSTEMS.COM