QC TRI PRO-7.0X
QuietCool Trident Pro Line

QuietCool
ADVANCED WHOLE HOUSE FANS

QC TRI PRO-7.0X Specifications

Air Flow	Hi: 7,015 CFM / Low: 5,548 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5,300 CFM / Low: 4,150 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2,338 SQFT to 3,507 SQFT
Energy Use	Hi: 1,147 Watts / Low: 797 Watts
Amps	Hi: 10.30 / Low: 7.15
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 54.3 / Low: 47.4
Minimum Attic Clearance	44"
Duct Diameter	24"
Duct Length	9 feet
Motor Head Diameter	24 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	9.36 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	97 lbs.
Box Dimensions	41" x 28" x 39"
In The Box	-QC TRI PRO-7.0X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Controls

For more information, visit our website at:
QUIETCOOLSYSTEMS.COM