



QC TRI PRO-1.5X QuietCool Trident Pro Line

QC TRI PRO-1.5X Specifications

Air Flow	1,498 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	1,110 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 499 SQFT to 749 SQFT
Energy Use	115 Watts
Amps	1.19
Motor Voltage	120 VAC, 60 Hz
# of Speeds	1
dBA	37.4
Minimum Attic Clearance	32"
Duct Diameter	14"
Duct Length	6 feet
Motor Head Diameter	14 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Included: 8 Hr Electronic Timer Optional: IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	2 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 14 1/4"
Removable Grille Outside Dimension	16" x 16"
Shipping Weight	43 lbs.
Box Dimensions	20" x 20" x 38"
In The Box	-QC TRI PRO-1.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM