XCI
ZONING SYSTEMS

SPECIFICATION SHEET

POC

Supply Air Damper 3-Wire Power Open/Power Close

- DEPENDABLE POWER OPEN/POWER CLOSE
- LED INDICATORS FOR FULL OPEN AND CLOSED POSITIONS
- LED INDICATORS FLASH WHEN BLADE IS MOVING
- INSULATION PAD UNDER MOTOR
- AVAILABLE SIZES: 6”, 7”, 8”, 9”, 10”, 12”, 14”, 16”, 18” & 20”
- LONG-LIFE ACTUATOR
- 5 YEAR FACTORY WARRANTY



GENERAL DESCRIPTION

The XCI POC-series low pressure two-position damper was developed for precise control of supply air in the HVAC duct system. The solid aluminum provides a lifetime of service. The damper actuator with built-in LED lights is designed for years of care-free operation. The power open/power close design guarantees precise control of supply air into each zone. Poron® rubber blade edges provides a positive seal for the blade. **Our gasketed damper blade is designed to compensate when installation conditions are not exact and the damper is not perfectly round.** Long-life nylon bushings insure a quiet, low friction operation of the damper. Heavy-duty galvanized steel ribbed cylinder provides strength to keep the damper round. One crimped end and one straight end allows for flexible installation. 30-Second operation to full open or closed position. A minimum open position can be set to bleed air for ventilation or duct balancing.

- **QUALITY DESIGN**
- **SUPERIOR FEATURES**
- **FLEXIBLE INSTALLATION**



SPECIFICATIONS

Power	24VAC, 2 VA typical (3 VA Max)
Actuator	XCI POCJ
	Brushless Motor Design
	18 in-lb Torque
	Power-Open/Power-Close
	30 Second Operation Cycle
	Max 90 Degree Travel
Indicator	LED Indicates Full Open or Close
Wiring	3 Screw Terminals
	PO, PC, Common
	Use 18/3 Solid Core Wire

XCI ZONING
4315 Huron Avenue
Lubbock TX 79407
www.xcizoning.com

Technical Support 866.924.2875
Sales/Information 866.924.4822
MADE IN USA

Rev 3.0 20200921

Part Number	D *Cylinder Diameter* (inches)	L Cylinder *Lengh* (Inches)
POC06	6	12
POC07	7	12
POC08	8	12
POC09	9	12
POC10	10	12
POC12	12	12
POC14	14	14
POC16	16	16
POC18	18	18
POC20	20	20

6” thru 10” - 24 ga. G90 Galvanized

12” thru 20” - 22 ga. G90 Galvanized



