XCI
ZONING SYSTEMS

SPECIFICATION SHEET

DAMPSLS AND DAMPSLB

Supply Air Damper 3-Wire Modulating Open and Close

- **DEPENDABLE MODULATING OPEN AND CLOSE**
- **ALTERNATE FOR OEM MODULATING DAMPERS**
- **90 DEGREE 15 SECOND FULL OPEN OR CLOSE CYCLE**
- **INSULATION PAD UNDER MOTOR REDUCES CONDENSATION**
- **STANDARD SIZES: 8 x 8 up to 30 x 30**
- **CUSTOM SIZES AVAILABLE**
- **LONG-LIFE ACTUATOR**
- **10 YEAR FACTORY WARRANTY**



GENERAL DESCRIPTION

The DAMPSLS AND DAMPSLB series low pressure modulating damper was developed for precise control of supply air in the HVAC duct system. Rigid aluminum components provide a strong, yet lightweight construction. The damper actuator is designed for years of care-free operation. The modulating open and close design guarantees precise control of supply air into each zone. Long-life nylon gears drive the opposed blades open and closed. Opposed blade design reduces turbulence in the air stream. 15 Second operation to full open or closed position. End of shaft marked with high-visibility blade position indicator. Custom sizes are available.

FULL 10 YEAR FACTORY WARRANTY ON ALL PARTS. NO REGISTRATION REQUIRED!

- **QUALITY DESIGN**
- **SUPERIOR FEATURES**
- **FLEXIBLE INSTALLATION**



SPECIFICATIONS

Power	24VAC, 2 VA typical (3 VA Max)
Actuator	XCI POCI
	Brushless Motor Design
	10 in-lb Torque
	Modulating Open and Close
	15 Second Operation Cycle
	Max 90 Degree Travel
Wiring	3 Screw Terminals
	PO, PC, Common
	Use 18/3 Solid Core Wire

Note: This damper <u>WILL NOT</u> work with XCI EasyZone controllers.

XCI ZONING
4315 Huron Avenue
Lubbock TX 79407

Technical Support 866.924.2875
Sales/Information 866.924.4822

MADE IN USA