Product Sheet





AIRFLOW & ENVIRONMENTAL METER ABM-200

The ABM-200 Airflow & Environmental Meter is a small, portable, wireless smart tool that, when paired with a smart phone or tablet running the latest CPS Link, can measure, record and e mail a variety of indoor/ outdoor temperature, humidity, airflow or pressure conditions taken at residential or commercial job sites.

KEY FEATURES:

- On screen guidance to accurately measure and record test data:
 - Temperature differential, dry bulb, wet bulb
 - and feels like temperatures
 - Airflow velocity and volume
 - Relative humidity, dew point
 - Barometric pressure, air density
 - Indoor/outdoor conditions Wind speed/direction/gusts
- Test And Balance Report- Automatically generated from data collected.
- E-mail professional reports for work completed, and where located
- Client Lists Easy to enter and retain client contact information
- Cloud back up of data



Mount inside ABM EasyHood

Mount on EXP-64 extension pole

Mount on TRI-MINI tripod (sold separately) (sold separately)





CPS Global Headquarters

1010 East 31st Street Hialeah, Florida 33013 USA www.cpsproducts.com For more information call: In the U.S.A. (800) 277-3808 or (305) 687-4121 In Canada (905)358-3124 In Europe 323 281 30 40 In Australia 61 8 8340 7055 CPS reserves the right to make changes to, or discontinue any product or service identified in this publication without notice. CPS advises its customers to ensure they have obtained the latest and most current version of any relevant information before placing any orders. © CPS Products, Inc. All rights reserved.



ABM-200

SPECIFICATIONS

Wireless Connection Range	≤100 ft. (30.5 m)				
Airflow Volume	Range: 35-1200 CFM (59-2,038 M ³ /H)				
Velocity	Range: 44-12,320 fpm (13 - 3,755 mpm)	Accuracy: ±0.5%			
Pressure (mbar)	Range: 300-1100	Accuracy: ±0.12 mbar			
RH	Range: 0-85%	Accuracy: ±4%			
Temperature	Range: 0 °F to 140 °F (-18 °C to 60 °C)				
	Accuracy: ±0.7 °F (0.4 °C)				
Bluetooth Smart	\checkmark				
Auto Power Off	No connection or 30 sec after closing ap	р			
Battery Type	3.0V CR2450 coin cell lithium (remove/reinstall rubber	r skin to access battery compartment)			
Battery Life	> 500 hrs.				
CPS Link	Patented modular test and measurement system tech	nology (US Patent No. 9,043,161)			
Warranty	1 Year				
RH Temperature Bluetooth Smart Auto Power Off Battery Type Battery Life CPS Link	Range: 0-85% Range: 0°F to 140°F (-18°C to 60°C) Accuracy: ±0.7°F (0.4°C) ✓ No connection or 30 sec after closing ap 3.0V CR2450 coin cell lithium (remove/reinstall rubber > 500 hrs. Patented modular test and measurement system tech	Accuracy: ±4% p skin to access battery compartment)			

CONDITIONS MEASURED FOR INDOOR OR OUTDOOR TESTS

Environmental Condition	Outdoor Test	Indoor Test
Dry Bulb	~	\checkmark
Web Bulb	✓	\checkmark
Feels Like	~	\checkmark
Relative Humidity	~	~
Dew Point	~	✓
Barometric Pressure	✓	\checkmark
Air Density	\checkmark	\checkmark
Wind Speed	~	
Wind Direction	✓	
Maximum Wind Gust	~	



ABM-200 packed in clamshell (included)



EASY ON-SCREEN GUIDANCE TO RECEIVE, STORE & SEND DATA



PACKAGING	CI	LAMSHE		INTERMEDIATE CARTON			MASTER CARTON					
	LxWxH	Weight	Meter Qty	Bar Code	L×W×H	Weight	Meter Qty	Bar Code	LxWxH	Weight	Meter Qty	Bar Code
ABM-200	5.00 x 2.40 x 1.00 inches (127 x 61 25 mm)	0.22 lb 0.10 kg	1	850470006022	7.00 x 5.80 x 5.80 inches (178 x 147 x 147 mm)	2.93 lb 1.33 kg	12	30850470006023 ABM-200-C	12.60 x 7.70 x 12.70 inches (320 x 196 x 323 mm)	12.00 lb 5.44 kg	48	20850470006026 ABM-200-MC

Designed for use with APPLE® products. APPLE® is a registered trademark in the United States and other countries. Designed for use with Android® products. Android® is a registered trademark in the United States and other countries.