



fantech[®]
a systemair company

Be in Control

Fresh Air Appliance Controls for Your Build



TABLE OF CONTENTS

Introduction.....	3
Total Volatile Organic Compounds (TVOC) Sensing Controllers.....	4
Multi-Function Controllers.....	6
Timers.....	8
Compatibility.....	10

LEVEL UP YOUR FRESH AIR APPLIANCE

At Fantech, we help you see what solution gets you clean air and why and where you might want to go beyond that to achieve a healthier home and ensure your customer's health and comfort.

We know that a healthy home starts with a ventilation system that brings in fresh air and controls the Indoor Air Quality (IAQ). We've got amazing controls to help you get the most out of your Fresh Air Appliance.

GOOD



ECO-Feel[®]

TVOC sensing controller, ECO-mode, w/o display, 4 wires



- Pre-programmed to run continuously on ECO Mode.
- Allows your system to operate around your home's needs and makes sure there is extra ventilation when you need it most - when you cook, clean or during large family gatherings.

BEST



ECO-Touch® IAQ

TVOC sensing controller, multi-function, touchscreen, 4 wires



- Recognizes presence of cleaning solvents, cooking odors or various compounds during large family gatherings
- Increases appliance's airflow capacity based on the total VOC levels
- Can be customized based on user preferences

GOOD



EDF3

Electronic controller, multi-function, push button



An electronic wall control that is compatible with all Fantech Fresh Air Appliances.

This control activates the system on 3 possible modes of operation:

- **ECONO** Continuous operation in ventilation mode at low or medium speed.
- **20 MIN/H** 20 minutes ON, 40 minutes OFF Intermittent (Yellow)
- **CONT** Continuous high speed in ventilation or recirculation mode.
- **OFF** Standby mode, both fans off

BEST



EDF8

Electronic controller, multi-function, display



This control activates the system on 3 possible modes of operation:

- Ventilation Mode - Removes stale air from inside your home and replaces it with fresh outdoor air
- Recirculation Mode - Takes air from areas of your home and redistributes it to other rooms. No outdoor air is introduced into the home
- Standby Mode - Inactive unless the indoor relative humidity is above the setpoint on the control

The fan speed can be selected.- Reduced, Medium, Normal or 20min/h



RTS4

Push button 20/40/60 min timer, wired



- Easy bathroom exhaust solution. Exhaust musty bathroom humidity while reintroducing fresh, pre-conditioned air to your living area.
- Designed to fit in a single-gang box
- Ideal for retrofit applications



RTS-W

Push button 20/40/60 min timer, wireless
RTS-W must be paired with ECO-Touch® IAQ



- Easy bathroom exhaust solution. Exhaust musty bathroom humidity while reintroducing fresh, pre-conditioned air to your living area.
- Designed to fit in a single-gang box
- Ideal for retrofit applications
- Wireless communication to ECO-Touch® IAQ (only) can range up to 50 feet

Finding the perfect pair is easy!

No matter what you need for your build, Fantech has you covered. Controllers are compatible with all Fantech Fresh Air Appliances, equipped with a 5-pin connector on the control board and manufactured after January 2019 with the exception of SE704N, SH704 and VH704.



Customer Support:
USA 800.747.1762 • USsupport@fantech.net
CANADA 800.565.3548 • CANADAsupport@fantech.net

Distributed Locally by:

Systemair Inc. reserves the right to modify, at any time and without notice, any or all of its products' features, designs, components and specifications to maintain their technological leadership position.

Zephyr Creative • March 2022, E1996

