PART NUMBER 0043860

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ● SMART	WIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9
CABLE SPECIFICATIONS	22 AWG 4 Graduates Dave Grades New Childred Discuss JUL Listed C(UL)UG CMD
DESCRIPTION	22 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION COLOR CODE	Low-Smoke PVC .008"
LAY LENGTH	Black/White/Red/Green
SHIELD	2.5" LHL (approx. 4.8 TPF) N/A
DRAIN WIRE	N/A N/A
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Green Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS
MARKING	MADE IN THE USA
OVERALL DIAMETER	.145" Nom.
CABLE WEIGHT	16 Lbs/Mft.
CAPACITANCE	20 pF/Ft. Nom.
IMPEDANCE	94 Ohms
DC RESISTANCE	16.9 Ohms/Mft. maximum @ 20 C
TEMPERATURE RATING	0 C to 75 C / 300 Volt
INDUSTRY STANDARDS	
FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA

All specifications referenced are nominal measurements unless otherwise noted.

