

YELLOW JACKET®

Series 41 2-Valve Manifold with 2-1/2" (63.5 mm) Gauges - °F



Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

Flutterless™ technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings.

Sliding double "O" ring pistons reduces wear. Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B).

Limited lifetime warranty on manifold bar and valves - not gauges. See warranty information for details.

Made in the USA



Box	Clamshell			
UPC#	UPC#	Description - °F/°C - Solar Gauges	Scale	Refrigerant
	41612	Manifold only	bar/psi/MPa	R-22/134a/404A/
	41615	With 60" PLUS II™ standard fittings	bar/psi/MPa	407C/409A/410A/ 438A/507
UPC#	UPC#	Description - °F - Red/Blue	Scale	Refrigerant
41213	41212	Manifold only	psi	
	-	With 36" PLUS II™ standard fittings	psi	
41220	-	With 48" PLUS II™ standard fittings	psi	
	41215	With 60" PLUS II™ standard fittings	psi	
	41219	With 72" PLUS II™ standard fittings	psi	R-12/22/502
	44215	With 60" PLUS II™ SealRight fittings	psi	
44219	-	With 72" PLUS II™ SealRight fittings	psi	
42215	-	With 60" PLUS II™ compact ball valve fittings	psi	
42219	-	With 72" PLUS II™ compact ball valve fittings	psi	
NEW	41202	Manifold only	psi	
	41209	With 36" PLUS II™ standard fittings	psi	R-22/134a/404A
	41211	With 60" PLUS II™ standard fittings	psi	
41313	41312	Manifold only	psi	
	-	With 36" RYB	psi	
41311	-	With 48" RYB	psi	
	41315	With 60" PLUS II™ standard fittings	psi	
	41319	With 72" PLUS II™ standard fittings	psi	
43313	-	With 36" PLUS II™ standard fittings	psi	
44313	-	With 36" PLUS II™ SealRight fittings	psi	R-134a/404A/507
	44315	With 60" PLUS II™ SealRight fittings	psi	
44319	-	With 72" PLUS II™ SealRight fittings	psi	
42315	-	With 60" PLUS II™ compact ball valve fittings	psi	
	41712	Manifold only	bar/psi	
	41709	With 60" PLUS II™ standard fittings	bar/psi	
41715*	-	With 60" PLUS II™ standard fittings for R-410A	bar/psi	
41710	-	With HCA 60" PLUS II™ standard fittings	bar/psi	R-410A
41702	-	With HCABV 60" PLUS II™ standard fittings	bar/psi	
42715	-	With 60" PLUS II™ compact ball valve fittings	bar/psi	
41711*	-	With 60" PLUS II™ compact ball valve fittings for R-410A	bar/psi	

* Special R-410A hose - R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.

Distributed by:

Ritchie Engineering Co., Inc.
 YELLOW JACKET Products Division
 10950 Hampshire Avenue South
 Bloomington, MN 55438-2623 USA
 Phone: (800)769-8370 or
 (952)943-1333
 e-mail: custserv@yellowjacket.com
www.yellowjacket.com

