# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name Lithium-Ion Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lithium-Ion Battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Applicant Name Klein Tools Asia Ltd.

Address RM 608, Houston Centre, 63 Mody Road, Tsim Sha Tsui, Kowloon Hong Kong

**Applicant Phone Number** 

Phone: 852-21533161

E-mail: gyeung@kleintools.com

Supplier Name LG Chemical Limited

Supplier Address Twin Tower Youido-Dong, Youngdeungpo-Ku Seoul, Korea

Supplier Phone Number

Phone: + 82-2-3773-7256

### 2. HAZARDS IDENTIFICATION

# Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

## GHS Label elements, including precautionary statements

# **Emergency Overview Danger**

#### Signal word Hazard Statements

Cause skin irritation
Causes serious eye irritation
Suspected of causing cancer
May cause an allergic skin reaction



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance Silver Physical State Solid containing liquid Odor Odorless

## **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Wear eye/face protection

## **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

## Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Technolo

If eye irritation persists: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

#### **Unknown Toxicity**

# Other information

Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

## Interactions with Other Chemicals

No information available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight %
Lithium Cobalt Oxide	12190-79-3	34.8
Carbon black	1333-86-4	0.3
1,1-Difluoroethylene polymer	24937-79-9	1.5
Graphite	7782-42-5	21.4
Sodium carboxymethyl cellulose	9004-32-4	0.1
Styrene-Butadiene polymer	9003-55-8	0.2
Phosphate(1-), hexafluoro-, lithium	21324-40-3	2
Ethylene carbonate	96-49-1	3.5
Ethyl methyl carbonate	623-53-0	3.5
Diethyl carbonate	105-58-8	2.9
Copper	7440-50-8	13.8
Copper foil	7440-50-8	1.1
Aluminum	7429-90-5	13.8
Aluminum foil	7429-90-5	1.1

## 4. FIRST AID MEASURES

First aid	d measures
Genera	I Advice

First aid is upon rupture of sealed battery. Show this safety data sheet to

the doctor in attendance

Rinse immediately with plenty of water, also under the eyelids, for at least **Eye Contact** 

15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops and persists. Do not rub affected area

Wash off immediately with soap and plenty of water for at least 15 **Skin Contact** 

minutes. In the case of skin irritation or allergic reactions see a physician.

May cause an allergic skin reaction.

Inhalation Remove to fresh air. If symptoms persist, call a physician. Get medical

attention immediately if symptoms occur.

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of Ingestion

water. Never give anything by mouth to an unconscious person. Call a

physician.

Self-protection of the first

aider

Avoid contact with skin, eyes or clothing. Use personal protective

equipment as required. Wear personal protective clothing (see section 8)

Most important symptoms and effects, both acute and delayed

**Most Important Symptoms** 

and Effects

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Itching, Rashes, Hives.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically

#### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous Combustion Products** 

**Explosion Data** 

Sensitivity to Mechanical Impact No. Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use

personal, protective equipment as required. Evacuate personnel to safe

areas

Other Information Refer to protective measures listed in Sections 7 and 8

**Environmental Precautions** 

**Environmental Precautions** Refer to protective measures listed in Sections 7 and 8.

Methods for cleaning up Pick up and transfer to properly labeled containers

Methods for Containment Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** In case of rupture. Use personal protection equipment. Avoid contact with

skin, eyes or clothing.

#### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Reference No.: CTL1703308011-SDS <u>Control parameters</u> Exposure Guidelines

Chemical Name	ACGIH TLV	OSHAPEL	NIOSH IDLH
Lithium Cobalt Oxide 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>		
Graphite	TWA: 2 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	respirable fraction all forms except graphite fibers	synthetic TWA: 5 mg/m³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume TWA: 1 mg/ mg/m³ Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	Cy	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m³ F TWA: 2.5 mg/m³ dust (vacated) TWA: 2.5 mg/m³	
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL:

Occupational Safety and Health

Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v.

OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national

exposure control parameters

**Appropriate engineering controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur:. Wear safety glasses with side shields (or

goggles). None required for consumer use.

**Skin and Body Protection** Wear protective gloves and protective clothing. Long sleeved clothing.

Impervious gloves

Respiratory Protection No protective equipment is needed under normal use conditions. If

exposure limits are exceeded or irritation is experienced, ventilation and

evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do

not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks

and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## **Physical and Chemical Properties**

Physical State Solid containing liquid

Appearance Silver Odor Odorless

Color No information available Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/</u> Method
рН	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit Vapor pressure	No data available No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	No data available	None known

**Decomposition temperature**No data available
None known

Kinematic viscosityNo data availableNone knownDynamic viscosity0.00001None known

Explosive propertiesNo data availableOxidizing PropertiesNo data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

**Particle Size Distribution** 

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

None known based on information supplied.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

# **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or

supplied information In case of rupture

Inhalation Specific test data for the substance or mixture is not available.

Corrosive by inhalation.(based on components).

Eye Contact Specific test data for the substance or mixture is not available.

Expected to be and irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye

irritation.

Skin Contact Specific test data for the substance or mixture is not available.

Expected to be an irritant based on components. Irritating to skin.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion

may cause irritation to mucous membranes. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea. May

be harmful if swallowed. (based on components).

**Component Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg ( Rat )	-	-
Carbon black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Sodium carboxymethyl cellulose	-	-	> 5800 mg/m₃ ( Rat ) 4 h

Information on toxicological effects

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes.

Coughing and/ or wheezing. Itching. Rashes Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause

sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects No information available

Carcinogenicity The table below indicates whether each agency has listed any

ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	<b>A</b> 3	Group 2B		X
Carbon black 1333-86-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X- Present

Reproductive Toxicity Contains a known or suspected reproductive toxin

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated

exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity No known effect based on information supplied. Contains a known

or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

May cause adverse liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Reproductive System. Blood Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Lungs. Nasal cavities.

Cardiovascular system. Systemic Toxicity. Liver.

**Aspiration Hazard** No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

ATEmix (dermal)
ATEmix (inhalation-dust/mist)

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemica I Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganism s	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchnerie lla subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L
Carbon	CO A			24h EC50: >
black 1333-86-4	The		E A	5600 mg/L

## Persistence and Degradability

No information available.

## **Bioaccumulation**

No information available

#### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

**Disposal methods** Should not be released into the environment.

**Contaminated Packaging** Dispose of in accordance with federal, state and local regulations.

## California Hazardous Waste Codes 141

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	To
12190-79-3	xic
Aluminum foil	lgnitable
7429-90-5	powder
Aluminum	lgnitable
7429-90-5	powder
Copper 7440-50-8	To xic

## 14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as"Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT NOT REGULATED Proper Shipping Name NON REGULATED Hazard Class N/A Not regulated **MEX** Not regulated ICAO Not regulated IATA Not regulated Proper Shipping Name Not regulated Hazard Class N/A IMDG/IMO Not regulated Proper Shipping Name NON-REGULATED PER SP 188 **Hazard Class** N/A EmS No. F-A, S-I Not regulated Not regulated AND Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA** Complies

All components are listed either on the DSL or NDSL. TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372  Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
--	--------	----------	-------------------------------------

- 1	51010100 Non 012110000011 020					
	Lithium Cobalt Oxide (CoLiO2)	12190-79-3	30~40	0.1		
	Aluminum foil	7429-90-5	1~5	1.0		
	Aluminum	7429-90-5	5~15	1.0		
	Copper	7440-50-8	5~15	1.0		

## SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden release of pressure hazardNoReactive HazardNo

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cop per 7440-50-8	+4:	x	х	

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5	ROLL		ユ

## **US State Regulations**

## **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

Chemical	California Proposition 65
Carbon black - 1333-86-4	Carcinogen

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode	Illinois
Lithium Cobalt Oxide (CoLiO2)	Х	Sting 1	X	Х	Х
Graphite 7782-42-5	Х	X	Х		
Carbon black 1333-86-4	X	Х	Х		Х
Copper 7440-50-8	Х	Х	Х	Х	Х
Aluminum foil 7429-90-5		Х		Х	
Aluminum 7429-90-5	X	Х	Х	Х	
Ethylene carbonate 96-49-1		Х	Х		
Diethyl carbonate 105-58-8	X	Х	Х		

## International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphite		Mexico: TWA= 2 mg/m <sup>3</sup>
7782-42-5 (15~25%)		
Copper		Mexico: TWA= 1 mg/m <sup>3</sup>
7440-50-8 (5~15%)		Mexico: TWA= 0.2 mg/m <sup>3</sup>
		Mexico: STEL= 2 mg/m <sup>3</sup>
Aluminum foil		Mexico: TWA= 10 mg/m <sup>3</sup>
7429-90-5 (1~5%)		
Aluminum		Mexico: TWA= 10 mg/m <sup>3</sup>
7429-90-5 (5~15%)		
Carbon black		Mexico: TWA 3.5 mg/m <sup>3</sup>
1333-86-4(0.1~0.5%)		Mexico: TWA 3.5 mg/m <sup>3</sup> Mexico: STEL 7 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### **WHMIS Hazard Class**

Non-controlled

## 16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and

Chemical Hazards -HMIS Health Hazards 0

Flammability 0 Physical Hazard 0

**Personal Protection** 

Prepared By E-filliate Incorporated

**Issuing Date Revision Date** 

07-Apr-2017

**Revision Note** No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and

is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

esting Techno End of Safety Data Sheet

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name Lithium-Ion Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lithium-Ion Battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Applicant Name Klein Tools Asia Ltd.

Address RM 608, Houston Centre, 63 Mody Road, Tsim Sha Tsui, Kowloon Hong Kong

**Applicant Phone Number** 

Phone: 852-21533161

E-mail: gyeung@kleintools.com

Supplier Name LG Chemical Limited

Supplier Address Twin Tower Youido-Dong, Youngdeungpo-Ku Seoul, Korea

Supplier Phone Number

Phone: + 82-2-3773-7256

### 2. HAZARDS IDENTIFICATION

# Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2			
Serious eye damage/eye irritation	Category 2			
Carcinogenicity	Category 2			
Specific target organ toxicity (repeated exposure)	Category 1			

## GHS Label elements, including precautionary statements

# **Emergency Overview Danger**

#### Signal word Hazard Statements

Cause skin irritation
Causes serious eye irritation
Suspected of causing cancer
May cause an allergic skin reaction



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance Silver Physical State Solid containing liquid Odor Odorless

## **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Wear eye/face protection

## **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

## Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Technolo

If eye irritation persists: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

#### **Unknown Toxicity**

# Other information

Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

## Interactions with Other Chemicals

No information available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight %
Lithium Cobalt Oxide	12190-79-3	34.8
Carbon black	1333-86-4	0.3
1,1-Difluoroethylene polymer	24937-79-9	1.5
Graphite	7782-42-5	21.4
Sodium carboxymethyl cellulose	9004-32-4	0.1
Styrene-Butadiene polymer	9003-55-8	0.2
Phosphate(1-), hexafluoro-, lithium	21324-40-3	2
Ethylene carbonate	96-49-1	3.5
Ethyl methyl carbonate	623-53-0	3.5
Diethyl carbonate	105-58-8	2.9
Copper	7440-50-8	13.8
Copper foil	7440-50-8	1.1
Aluminum	7429-90-5	13.8
Aluminum foil	7429-90-5	1.1

## 4. FIRST AID MEASURES

First aid	d measures
Genera	I Advice

First aid is upon rupture of sealed battery. Show this safety data sheet to

the doctor in attendance

Rinse immediately with plenty of water, also under the eyelids, for at least **Eye Contact** 

15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops and persists. Do not rub affected area

Wash off immediately with soap and plenty of water for at least 15 **Skin Contact** 

minutes. In the case of skin irritation or allergic reactions see a physician.

May cause an allergic skin reaction.

Inhalation Remove to fresh air. If symptoms persist, call a physician. Get medical

attention immediately if symptoms occur.

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of Ingestion

water. Never give anything by mouth to an unconscious person. Call a

physician.

Self-protection of the first

aider

Avoid contact with skin, eyes or clothing. Use personal protective

equipment as required. Wear personal protective clothing (see section 8)

Most important symptoms and effects, both acute and delayed

**Most Important Symptoms** 

and Effects

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Itching, Rashes, Hives.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically

#### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous Combustion Products** 

**Explosion Data** 

Sensitivity to Mechanical Impact No. Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use

personal, protective equipment as required. Evacuate personnel to safe

areas

Other Information Refer to protective measures listed in Sections 7 and 8

**Environmental Precautions** 

**Environmental Precautions** Refer to protective measures listed in Sections 7 and 8.

Methods for cleaning up Pick up and transfer to properly labeled containers

Methods for Containment Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** In case of rupture. Use personal protection equipment. Avoid contact with

skin, eyes or clothing.

#### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Reference No.: CTL1703308011-SDS <u>Control parameters</u> Exposure Guidelines

Chemical Name	ACGIH TLV	OSHAPEL	NIOSH IDLH
Lithium Cobalt Oxide 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>		
Graphite	TWA: 2 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	respirable fraction all forms except graphite fibers	synthetic TWA: 5 mg/m³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume TWA: 1 mg/ mg/m³ Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	Cy	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m³ F TWA: 2.5 mg/m³ dust (vacated) TWA: 2.5 mg/m³	
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL:

Occupational Safety and Health

Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v.

OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national

exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur:. Wear safety glasses with side shields (or

goggles). None required for consumer use.

**Skin and Body Protection** Wear protective gloves and protective clothing. Long sleeved clothing.

Impervious gloves

Respiratory Protection No protective equipment is needed under normal use conditions. If

exposure limits are exceeded or irritation is experienced, ventilation and

evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do

not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks

and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## **Physical and Chemical Properties**

Physical State Solid containing liquid

Appearance Silver Odor Odorless

Color No information available Odor Threshold No information available

Property	<u>Values</u>	Remarks/
		<u>Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	No data available	None known

**Decomposition temperature**No data available
None known

Kinematic viscosityNo data availableNone knownDynamic viscosity0.00001None known

Explosive propertiesNo data availableOxidizing PropertiesNo data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

**Particle Size Distribution** 

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

None known based on information supplied.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

# **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or

supplied information In case of rupture

Inhalation Specific test data for the substance or mixture is not available.

Corrosive by inhalation.(based on components).

Eye Contact Specific test data for the substance or mixture is not available.

Expected to be and irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye

irritation.

Skin Contact Specific test data for the substance or mixture is not available.

Expected to be an irritant based on components. Irritating to skin.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion

may cause irritation to mucous membranes. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea. May

be harmful if swallowed. (based on components).

**Component Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg ( Rat )	-	-
Carbon black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Sodium carboxymethyl cellulose	-	-	> 5800 mg/m₃ ( Rat ) 4 h

Information on toxicological effects

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes.

Coughing and/ or wheezing. Itching. Rashes Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause

sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects No information available

Carcinogenicity The table below indicates whether each agency has listed any

ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	<b>A</b> 3	Group 2B		X
Carbon black 1333-86-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X- Present

Reproductive Toxicity Contains a known or suspected reproductive toxin

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated

exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity No known effect based on information supplied. Contains a known

or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

May cause adverse liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Reproductive System. Blood Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Lungs. Nasal cavities.

Cardiovascular system. Systemic Toxicity. Liver.

**Aspiration Hazard** No information available.

<u>Numerical measures of toxicity Product Information</u>
The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

ATEmix (dermal)
ATEmix (inhalation-dust/mist)

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemica I Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganism s	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchnerie lla subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L
Carbon	(0)		5	24h EC50: >
black 1333-86-4	She		节	5600 mg/L

# Persistence and Degradability

No information available.

## Bioaccumulation

No information available

#### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods Should not be released into the environment.

Dispose of in accordance with federal, state and local regulations. **Contaminated Packaging** 

## California Hazardous Waste Codes 141

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	To
12190-79-3	xic
Aluminum foil	lgnitable
7429-90-5	powder
Aluminum	lgnitable
7429-90-5	powder
Copper 7440-50-8	To xic

## 14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as"Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT NOT REGULATED Proper Shipping Name NON REGULATED Hazard Class N/A Not regulated **MEX** Not regulated ICAO Not regulated IATA Not regulated Proper Shipping Name Not regulated Hazard Class N/A IMDG/IMO Not regulated Proper Shipping Name NON-REGULATED PER SP 188 **Hazard Class** N/A EmS No. F-A, S-I Not regulated Not regulated AND Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA** Complies

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372  Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
--	--------	----------	-------------------------------------

- 1	51010100 Non 512110000011 020				
	Lithium Cobalt Oxide (CoLiO2)	12190-79-3	30~40	0.1	
	Aluminum foil	7429-90-5	1~5	1.0	
	Aluminum	7429-90-5	5~15	1.0	
	Copper	7440-50-8	5~15	1.0	

## SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden release of pressure hazardNoReactive HazardNo

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cop per 7440-50-8	+4:	х	х	

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5	ROLL		ユ

## **US State Regulations**

## **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

Chemical	California Proposition 65
Carbon black - 1333-86-4	Carcinogen

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode	Illinois
Lithium Cobalt Oxide (CoLiO2)	Х	Sting 1	X	Х	Х
Graphite 7782-42-5	Х	X	Х		
Carbon black 1333-86-4	X	Х	Х		Х
Copper 7440-50-8	Х	Х	Х	Х	Х
Aluminum foil 7429-90-5		Х		Х	
Aluminum 7429-90-5	X	Х	Х	Х	
Ethylene carbonate 96-49-1		Х	Х		
Diethyl carbonate 105-58-8	X	Х	Х		

## International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphite		Mexico: TWA= 2 mg/m <sup>3</sup>
7782-42-5 (15~25%)		
Copper		Mexico: TWA= 1 mg/m <sup>3</sup>
7440-50-8 (5~15%)		Mexico: TWA= 0.2 mg/m <sup>3</sup>
		Mexico: STEL= 2 mg/m <sup>3</sup>
Aluminum foil		Mexico: TWA= 10 mg/m <sup>3</sup>
7429-90-5 (1~5%)		
Aluminum		Mexico: TWA= 10 mg/m <sup>3</sup>
7429-90-5 (5~15%)		
Carbon black		Mexico: TWA 3.5 mg/m <sup>3</sup>
1333-86-4(0.1~0.5%)		Mexico: TWA 3.5 mg/m <sup>3</sup> Mexico: STEL 7 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### **WHMIS Hazard Class**

Non-controlled

## 16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and

Chemical Hazards -HMIS Health Hazards 0

Flammability 0 Physical Hazard 0

**Personal Protection** 

Prepared By E-filliate Incorporated

**Issuing Date Revision Date** 

07-Apr-2017

**Revision Note** No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and

is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

esting Techno End of Safety Data Sheet