


**RGAPAXX, RGAPBXX**  
**Infinity® Return Air Purifier**  
**Size 1625**



Turn to the experts

## Product Data



A200506



ZERO OZONE EMISSIONS –  
MEASURED OZONE EMISSIONS  
FROM INFINITY® RETURN AIR  
PURIFIER DURING USE PHASE  
DOES NOT EXCEED 0.005 PPM  
AS TESTED ACCORDING TO  
CSA C22.2 NO. 187-20.  
UL.COM/ECV



A200424CA

The Infinity® Return Air Purifier is designed for use in the return air duct of a forced air heating, cooling, and ventilation system.

It combines superior filtration efficiency, MERV 15<sup>1</sup>, with pathogen-killing technology to deliver maximum air purification.

The Infinity® Return Air Purifier is designed to require minimal maintenance. Maintenance is limited to the replacement of the air purification cartridge and inspection/brush cleaning of the ionization array. Frequency of air purifier cartridge replacement and cleaning of the ionization array may vary depending on ductwork design and local environmental conditions.

### FEATURES / Benefits

**Filtration Performance** — High efficiency MERV 15<sup>1</sup>, meets flow 0.10 @ 800 CFM

**Purification Performance** — Featuring patented Captures & Kills® technology, the Infinity® air purifier offers proven, third-party tested effectiveness with a 99% inactivation of captured viruses and germs when used as instructed, including:<sup>2</sup>

- Coronavirus
- Common cold surrogate
- Bacteria that causes strep throat
- Human influenza

**Works With** —

- Gas Furnace Equipment – RGAPAXX1625
- Fan Coil Equipment – RGAPBXX1625

**Simple Maintenance** — Virtually no cleaning required. Simply change purifier cartridge periodically and brush off array.

**Easy to Install** — Adjustable L-brackets to fit 2 x 4 and 2 x 6 joists.

**Replaceable Filters** — Pull down access to replace filters from inside the home.

**Solid-State Power Supply** — Power supply is a highly reliable, dual voltage compatible, state-of-the-art, solid-state device.

**Durable Cabinet** — Heavy-gauge steel cabinet and frame.

**Agency Listed** — Model RGAP Air Purifier is UL (Canada and US) listed.

1. MERV is a filter efficiency standard ranging from 1 to 16 (higher MERV = higher efficiency). The Infinity air purifier achieves a MERV 15 rating based on third-party testing (2012) showing 95% of particles size 1.0 to 3.0 microns captured and 85% of particles size 0.3 to 1.0 microns captured.


2. The Infinity air purifier has demonstrated effectiveness against the murine coronavirus, based on third-party testing (2020) showing a >99% inactivation, which is a virus similar to the human novel coronavirus (SARS-CoV-2) that causes COVID-19. Therefore, the Infinity air purifier can be expected to be effective against SARS-CoV-2 when used in accordance with its directions for use. Third-party testing (2012, 2007) also shows ≥99% inactivation for the type of virus that causes common colds, Streptococcus pyogenes and human influenza. Airborne particles must flow through your HVAC system and be trapped by the filter to be inactivated at 99%.

## RGAP(A,B)XX1625 Specifications, Accessories, and Dimensions

SPECIFICATIONS	
<b>Weight, shipping — Lbs (kg)</b>	60 (27)
<b>Filtration Efficiency *</b>	MERV 15
<b>Filter Media Surface Area — Sq. Ft. (Sq. Meter)</b>	50.8 (4.7)
<b>Replacement Filter Dimensions — Inches (cm)</b>	17.3 x 24.9 x 2.6 (44 x 63 x 7)
<b>Electrical</b>	Dual voltage power supply 115/60/1, 208-230/60/1 built into door. 6 ft. conduit with (3) 18AWG wires with quick connect terminals
<b>Max Power Consumption</b>	22 Watts
<b>Purification Performance</b>	99% inactivation for murine coronavirus, human influenza virus, common cold virus, streptococcus bacteria
<b>Cabinet &amp; Color</b>	G60 steel, Granite Grey, RoHS compliant
<b>Maximum Air Flow — CFM (LPS) *</b>	1600 (755)
<b>Dust Holding Capacity @ 0.5 in wg at max airflow (grams ASHRAE Dust)</b>	37
<b>Ozone Produced (max allowed is 0.05 PPM)</b>	Maximum ozone produced at 375 CFM is 0.014499 PPM.† Maximum ozone produced at 2200 CFM is 0.002231 PPM.†
INITIAL PRESSURE DROP WITH CLEAN FILTER	
CFM (LPS)	In. wg (pa)
400 (189)	0.05 (12)
600 (283)	0.08 (21)
800 (378)	0.13 (33)
1000 (472)	0.19 (47)
1200 (566)	0.26 (64)
1400 (661)	0.33 (82)
1600 (755)	0.42 (105)
1800 (850)	-
2000 (944)	-
2200 (1038)	-
ACCESSORIES	
<b>Replacement Filter P/N (2-pk)</b>	AGAPXCAR1625-A02
<b>Safety Screen Accessory</b>	KIT170000
<b>Safety Screen Dimensions — Inches (cm)</b>	17.49 x 24.40 x 1.75 (44.4 x 62.0 x 4.4)
<b>Filter Enhancement Module (FEM)</b>	KIT145000
<b>Power Supply Assembly</b>	KIT159000
<b>Current Sensing Relay Kit</b>	HN72ZA001
<b>Service Quick Kit</b>	344872-751 (Included standard with the RGAPBXX1625)
<b>Air Flow Sensor</b>	KIT160000 (Included standard with the RGAPBXX1625)
<b>Flow Sensor Bypass</b>	KIT161000 (Included standard with the RGAPAXX1625)
<b>Safety Switch</b>	346811-401
<b>Gas Strut</b>	347055-401

\*. Per ASHRAE 52.2 2007

†. Meets EPA and CA limits based on CSA 22.2 #187-20



A200505