



FOGGER SERIES ULV COLD FOGGER

XPOWER's family of ULV (ultra-low volume) cold foggers offers you ultimate performance with a multitude of size and capacity to meet your sanitizing needs. Featuring a light and compact design, this unit is ideal for full coverage for office, restaurants/food services, schools, hospitals, senior centers, pet boarding, greenhouse, and commercial properties. The reservoir incorporates an easy fill/tight cap and a reservoir level window to monitor your liquid levels. Applying disinfectants, sanitizers, and other solutions have never been easier than using the XPOWER line of ULV cold foggers. With its powerful spray distance and ultra-small droplet size, XPOWER family of ULV Foggers is the industry leading choice for all your fogging needs.



F-8



F-16 F-8B Corded Models Cordless Rechargeable Models



F-16B







SPECIFICATIONS

			22	22	10	
		=			5	
MODEL NO.	F-8	F-8B	F-16	F-16B	F-18B	F-35B
VOLTZ/HERTZ	115V/60Hz	120V/60Hz	115V/60Hz	120V/60Hz	115V/60Hz	115V/60Hz
MOTOR	320W	280W	500W	350W	320W	320W
POWER	3 Amps	~	4 Amps	~	~	~
CHARGE TIME / RUN TIME	~	3 hrs / 16 mins	~	3 hrs / 32 mins	1+ hrs / 2+ hrs	2+ hrs / 3+ hrs
SPEEDS	1 Speed	1 Speed	2 Speed	1 Speed	2 Speed	1 Speed
CORD LENGTH	20 ft.	6 ft.	25 ft.	10 ft.	25 ft.	25 ft.
FLOW RATE	100 / 200ml/min	75 / 150 ml/min	250 / 350ml/min	200 / 250ml/min	200 / 250ml/min	200 / 250ml/min
SPRAYING DISTANCE	33+ ft.	25+ ft.	38+ ft.	30+ ft.	39+ ft.	39+ ft.
AVERAGE DROPLET SIZE	< 50 Micron	< 50 Micron	< 50 Micron	< 50 Micron	< 50 Micron	< 50 Micron
TANK CAPACITY	800ml (27 fl oz.)	600ml (20.2 fl oz.)	1600ml (54 fl oz.)	1200ml (40.4 fl. oz.)	1200ml (40.4 fl. oz.)	2500ml (84.5 fl. oz.)
BATTERY OPERATED	No	Yes	No	Yes	Yes	Yes
UNIT WEIGHT	4.85 Lbs.	4.4 Lbs.	6.1 Lbs.	5.73 Lbs.	6 Lbs.	5.73 Lbs.
UNIT DIMENSIONS (LXWXH)	12.1 x 6.4 x 7.8 in.	14.2 x 7.9 x 8.7 in.	14.6 x 6.8 x 8.3	14.6 x 6.8 x 8.3	14.6 x 6.8 x 8.3	19.1 x 7 x 8.5
HOUSING	PP	PP	PP	PP	PP	PP
THERMAL PROTECTION	Yes	Yes	Yes	Yes	Yes	Yes



WWW.XPOWER.COM