

Perfect Comfort Control At The Touch of Your Finger



GEN*V*

Manage your system from a single point with a simple & easy to use interface.

Simplify your management experience with GEN *V*, no complex software to learn, no PC or internet connection required. Control 20 zones per RTU or split-system.



Manage the entire system from one central HUB, no internet connection required

Control one zoned unit with up to 20 zone dampers per unit or control 20 standalone roof top units or split systems.



Color LCD touchscreens and intuitive menus make system management effortless



Ø

24 VAC output signal when the system is in the occupied mode. This signal can be connected to an economizer or any other device that requires an occupied signal



- Programmable fan scheduling to optimize air purification
- ADR / FDD for Title 24 compliance
- Simple daisy chain wiring from the GEN *V* stat to stat, with no home run wiring required
- No computer required for setup or management
 - Prioritize stats from the HUB with 0,1,2, or 3 votes
 - On board diagnostics streamlines troubleshooting

GEN V Controller



Simple daisy-chain control wiring

EzTouchV HUB Stat

Control the entire system from a single point, don't go to each stat



EzTouchX Zone Thermostat



Elegant design and high tech performance

GEN V

GEN V Configuration menu

Perfect Comfort Control At The Touch of Your Finger

The GEN V communicates with an EzTouchV HUB thermostat that allows easy configuration of the GEN V controller with up to 20 thermostats.

The GEN V can manage zone stats controlling modulating dampers or standalone stats that control RTU or split systems.

From the HUB thermostat you can monitor communications and operations of the entire system. Modify thermostat set points individually or globally, lock stats with 0° or +/-2°variance, set an individual or global schedule per zone, and vacation schedules.

The system operation supports ADR & FDD to meet Title 24 requirements.

FDD Alert

Image: state stat

Control zoned and multiple standalone units

Zone Overview

9:25 am 9:25 am :26 am :17 am **3** communication ok stat 01 72 75 70 type stat 02 71 75 70 temperature nd stag stat 03 🔥 69 75 70 occupied sp mode heat/coo set fan mode call set unit type status cool-to heat-to ect from menu zone overview stat 1 diagnostic

Diagnostics

Your alternative to costly & complex control systems The GEN *V* makes managing your facility easy and affordable!

REQUEST A QUOTE



Call (800) 228-2966 or get a quote at www.zonexproducts.com