
POLYKEN®



Professional Grade Duct Tape (Prt Metallic)



Backing: Metallized PE Coated Cloth

Adhesive: Rubber N/A Liner:

Colors: Metallic (Printed)

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing Bundling, patching, and mending environments
- General repair

Features Benefits

Metallized PE-Coated Cloth Backing	 Excellent balance of tensile strength and tearability
Natural Rubber Based Adhesive	Aggressive adhesion to rough surfacesSuperior holding power for hanging applications
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11.0 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101
Adhesion to Backing	48 oz/in	5.25 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000
Elongation	24%		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	5		
Flame Spread	10		
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

