



PRO1 SUBMITTAL SHEET

Job Name: _____ Location: _____ Date: _____

Purchaser: _____ Installer: _____

Submitted to: _____ For: ☐ RNC ☐ R&R ☐ Commercial

MODEL T751i

Universal - WIFI

2 Heat, 2 Cool Conventional

4 Heat, 2 Cool Heat Pump

Hardwire Only

Programmable Through App



This model features:

- 7 sq. inch display
- Blue backlight
- Glow in the dark light button
- Universal subbase
- Simple private label badge system
- Setpoint limits
- 24V power
- 5 Year warranty
- 5 minute compressor delay protection (selectable on or off)
- Customizable staging logic
- Separate heating and cooling swing (cycle rate) adjustments
- Auto Changeover

Specifications:

Application	2 Heat, 2 Cool Conventional / 4 Heat, 2 Cool Heat Pump
Programmability	Programmable Through App
Changeover	System Switch
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	Rc, Rh, Y, Y2, W2, W/E, G, B, O
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire)
Operating Ambient	32°F to +105°F (0°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D)
Warranty	5 year warranty



Google Play is a trademark of Google Inc.

Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.