AF 984

AF 984CT COLD TEMPERATURE FOIL/SCRIM/KRAFT TAPE

TYPICAL APPLICATIONS
- For sealing seams in scrim-reinforced duct insulation

PRODUCT FEATURES
- Foil/Scrim/Kraft (FSK) tape
- Lined
- Superior stability during extreme fluctuations in temperatures
- Wrinkle-free backing resists tearing
- Resists water vapor and smoke transmission

CONSTRUCTION
Backing: Aluminum foil/fiberglass scrim/kraft paper

Adhesive: Cold temperature, white acrylic-based adhesive

Liner: Non-contaminating, siliconized, flat, white, paper release liner

STANDARD WIDTHS
1.88 in; 2.83 in; 3.77 in

48 mm; 72 mm; 96 mm

STANDARD LENGTH
50 yd

46 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE
3 in

APPLICABLE STANDARDS
FSI 5/SDI 0

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS
Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR
Silver (SIL)

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	64 oz/in width	7.0 N/10 mm
Elongation	3%	3%
Service Temperature Range	-20 F to 260 F	-29 C to 127 C
Tensile	34 lbs/in width	59.5 N/10 mm
Thickness - With Liner	11.1 mils	0.28 mm
Thickness - Without Liner	7.4 mils	0.19 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtapetech.com
ISO 9001 CERTIFIED QUALITY SYSTEM
Shurtape is a registered trademark of Shurtape Technologies, LLC Form# TDS-AF-984-20240610