NAVAC

Empowering you to work smarter

MASTER SERIES

NRDC4M
4-Cylinder Recovery Unit

4 - Cylinder

A2L Compatible

2020 DEALER DESIGN AWARDS
theNEWS | GOLD

Industry Fastest

Scan to see recovery unit comparison sheet



Digital Backlit Display

Purge Function

Brushless DC Technology

Dual Oil-Free Compressors

3 High-Speed Cooling Fans

3/8" Inlet Port

1/4" Outlet Port

World's First DC Inverter 4-Cylinder Recovery Unit

Fastest · Most Powerful

4-Cylinder for Powerful Recovery
- Up to 40% faster than 2-cylinder unit
- Oversized inlet port for faster recovery

Large Digital Display
- Easy-to-read large LCD display
- Backlit for clarity

Super-Efficient Condenser
- Over-sized micro-channel coil
- 3 cooling fans

Dual Oil-Free Compressors
- Suitable for all commonly used refrigerants

Brushless DC Motor
- More efficient

Acceleration Knob Design
- To achieve faster vapor recovery

Model		NRDC4M			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500, R-1234YF Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R454B, R-502, R-509 Category V: R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V/Hz	115V/60Hz			
Motor	HP	1.5			
Max Current Draw	A	12			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi/38.5 bar			
UL Verified Recovery Rate (UL VERIFIED)	lbs/min (kg / min)		R-410A	R-22	R-134a
		Direct Vapor	1.06 (0.48)	0.99 (0.45)	0.84 (0.38)
		Direct Liquid	16.82 (7.63)	12.76 (5.79)	9.19 (4.17)
		Push/Pull Liquid	18.23 (8.27)	16.76 (7.60)	15.08 (6.84)
Inlet/Outlet Port	in	Inlet 3/8", Outlet 1/4"			
Dimension	in	17×10.7×12.2			
Weight	lbs	41.9			

2-YEAR WARRANTY