



Overview

The wall mounted stainless plate pickup ports are designed to be used in conjunction with any low differential pressure transmitter to provide an aesthetically pleasing building static reference point (pressure). When used in conjunction with a low differential pressure transmitter, the pickup ports provide excellent accuracy and reliability. For best results, make sure that the tubing is free of dirt, dust and condensation and that you keep the tubing run as short as possible to provide the best response time.

Applications: Monitoring Indoor Building Static Pressure in Commercial/Office Buildings, Clean Rooms, Isolation Rooms, Hospitals, Laboratories, Schools, etc.



Part Numbers

NSA-HH/SP-PUP-C

Specifications

Tubing Connections:	Barbed fitting accepts 3/16" ID flexible Poly tubing
Maximum Operating Pressure:	Filter: 150 psi (10.3 bar) Medical Tubing (A/10' Tube, A/20' Tube, A/100' Tube): 65 psi maximum at 73°F (23°C)
Operating Temperature Range:	-40° to 150°F (-40° to 66°C)
Storage Temperature Range:	-40° to 160°F (-40° to 71°C)
Wall Plate Material:	302 Series Stainless Steel
Wall Plate Color Finish:	Silver (Metallic) Brushed Stainless Steel
Foam Material Flammability Rating:	Cross-Linked Polyethylene FMUSS-302
Filter Material:	Nickel Plated Brass
Product Dimensions (L x W x D) Weight:	4.51" (11.5 cm) x 2.76" (7.00 cm) x 0.190" (0.48 cm) 0.16 lbs (0.073 kg)
Agency Approvals:	RoHS2, WEEE, Reach

Dimensional Drawing

