

QuietCool
ADVANCED WHOLE HOUSE FANS

QC STL PRO-1.5X RF Specifications

Airflow	1,479 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	1,040 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 439 SQFT to 739 SQFT
Energy Use	66.7 Watts
Amps	0.9
Motor Voltage	120 VAC, 60 Hz
# of Speeds	1
dBA	37.2
Minimum Attic Clearance	32"
Duct Diameter	14"
Duct Length	6 feet
Motor Head Diameter	14 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	1.98 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 14 1/4"
Removable Grille Outside Dimension	16" x 16"
Shipping Weight	43 lbs.
Box Dimensions	20" x 20" x 38"
In The Box	-QC STL PRO-1.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -6 Foot Duct -Accessory Bag -Wireless RF Control Kit



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Intertek
5020138

Rev. 10/2/24