

QuietCool
ADVANCED WHOLE HOUSE FANS

QC STL PRO-6.0X RF Specifications

Airflow	Hi: 5,587 CFM / Med: 4,262 CFM / Low: 3,428 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,030 CFM / Med: 3,070 CFM / Low: 2,440 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,862 SQFT to 2,794 SQFT
Energy Use	Hi: 462 Watts / Med: 210 Watts / Low: 113 Watts
Amps	Hi: 5.91 / Med: 2.90 / Low: 1.65
Motor Voltage	120 VAC, 60 Hz
# of Speeds	3
dBA	Hi: 49.3 / Med: 42.5 / Low: 38.5
Minimum Attic Clearance	42″
Duct Diameter	22″
Duct Length	9 feet
Motor Head Diameter	22 1/2″
Motor Head Length	13 1/2″
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16″ or 24″ on center
Minimum Suggested Attic Venting	7.45 SQ FT net free area
Ceiling Rough Opening	14 1/4″ x 36 1/4″
Removable Grille Outside Dimension	16″ x 38″
Shipping Weight	96 lbs.
Box Dimensions	41″ x 26″ x 39″
In The Box	-QC STL PRO-6.0X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Wireless RF Control Kit





For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Intertek
5020138

Rev. 10/2/24