QuietCool
ADVANCED WHOLE HOUSE FANS

QC TRI PRO-3.3X RF Specifications

Airflow	Hi: 3,216 CFM / Low: 2,890 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 2,450 CFM / Low: 2,230 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,072 SQFT to 1,608 SQFT
Energy Use	Hi: 323 Watts / Low: 274 Watts
Amps	Hi: 2.77 / Low: 2.36
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 49.4 / Low: 46.8
Minimum Attic Clearance	34"
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	4.29 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 22 1/4"
Removable Grille Outside Dimension	16" x 24"
Shipping Weight	55 lbs.
Box Dimensions	27" x 20" x 38"
In The Box	-QC TRI PRO-3.3X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -6 Foot Duct -Accessory Bag -Wireless RF Control Kit

For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Intertek
5020138

Rev. 10/2/24