QuietCool
ADVANCED WHOLE HOUSE FANS

QC TRI PRO-4.8X RF Specifications

Airflow	Hi: 4,428 CFM / Low: 3,436 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,260 CFM / Low: 2,570 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,476 SQFT to 2,214 SQFT
Energy Use	Hi: 555 Watts / Low: 417 Watts
Amps	Hi: 4.73 / Low: 3.58
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 49.4 / Low: 43.2
Minimum Attic Clearance	36″
Duct Diameter	18″
Duct Length	9 feet
Motor Head Diameter	18 1/2″
Motor Head Length	13 1/2″
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16″ or 24″ on center
Minimum Suggested Attic Venting	5.91 SQ FT net free area
Ceiling Rough Opening	14 1/4″ x 30 1/4″
Removable Grille Outside Dimension	16″ x 32″
Shipping Weight	75 lbs.
Box Dimensions	36″ x 22″ x 40″
In The Box	-QC TRI PRO-4.8X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Wireless RF Control Kit

For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Intertek
5020138

Rev. 10/2/24