

QC TRI PRO-6.0X RF
QuietCool Trident Pro Line

QuietCool
ADVANCED WHOLE HOUSE FANS

QC TRI PRO-6.0X RF Specifications

Airflow	Hi: 5,708 CFM / Low: 4,319 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,150 CFM / Low: 3,190 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,903 SQFT to 2,854 SQFT
Energy Use	Hi: 777 Watts / Low: 560 Watts
Amps	Hi: 6.90 / Low: 5.09
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 51.1 / Low: 44.1
Minimum Attic Clearance	42"
Duct Diameter	22"
Duct Length	9 feet
Motor Head Diameter	22 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	7.62 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	96 lbs.
Box Dimensions	41" x 26" x 39"
In The Box	-QC TRI PRO-6.0X Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Wireless RF Control Kit





For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Intertek
5020138

Rev. 10/2/24