STRUT LOCK ASSEMBLY

The Strut Lock Assembly is a fast, lockable solution for installing Dyn-O-Strut in single and multi-tiered arrangements, for HVAC and cable management. It is ideal for the suspension of rectangular duct, chilled beams, cable tray, unit heaters, etc. The ability to pre-fit the assembly into the strut channel on the ground, allows for minimal time working at heights. A threaded release cylinder allows for time saving height adjustment.

- **Works best in conjunction with Deep 1-5/8" x 1-5/8" Dyn-O-Strut and Shallow 13/16" x 1-5/8" Dyn-O-Strut**
- **Can be used with single or multi-tiered applications**
- **For vertical, static loads**
- **4:1 Safety Factor**
- **Quick to install and adjust**
- **Kit includes Strut Lock, zinc plated washer, flat washer and strut nut**
- **Strut Lock can be installed on the open or flat side of strut**

Item #	Code	Description	Packaged	Working Load*
31079	DSL2Z	Strut Lock Assembly for use with WC2 Wire Rope	10 sets/ bag	10-75 lbs. (5-34 kg)
31080	DSL3Z	Strut Lock Assembly for use with WC3 Wire Rope	10 sets/ bag	25-150 lbs. (12-68 kg)
31081	DSL4Z	Strut Lock Assembly for use with WC4 Wire Rope	10 sets/ bag	25-225 lbs. (12-102 kg)
*Safe Working Loads are based on a 4:1 Safety Factor				
**WARNING: Always ensure the anchor point or base material are suitable to support the intended load, at the installer's responsibility				

Duro Dyne Corporate Headquarters, Bay Shore, NY
631-249-9000 • Fax: 631-249-8346
Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
www.durodyne.com • E-mail: durodyne@durodyne.com

© Duro Dyne Corp.
Printed in USA 10/25/2021
BD030420