Central Air Conditioner/Heat Pump Soft Starters

PRODUCT
SoftStart Home™ soft starters: Modelo SSH6T and Modelo SSH3T

APPLICATION
6-ton (72,000 BTU) and 3-ton (32,000 BTU central air conditioners/heat pumps

POWER RATING
110VAC (90~135VAC) & 220VAC (187~226VAC), 1 phase

INDOOR/OUTDOOR
Indoor/Outdoor

ENCLOSURE MEDIUM
Module housing sealed in epoxy resin

ADVANTAGES
- Quiet A/C startup - no jarring thump, flickering lights or tripping breaker when A/C starts
- Low-amp startup reduces strain on compressor to help extend A/C life
- Helps start and run A/C on a backup generator
- Starts home A/C with solar energy system without straining battery power supply to other appliances
- Easier and quicker to install than other A/C soft starters

INSTRUCTIONS
Electronic version available at softstarthome.com/support

HAZMAT HAZARD
None

AGENCY LISTINGS
CE

c ETL US LISTED 5032133 Intertek



SSH6T



SSH3T

SKU SPECIFIC METRICS

UPC:	**SSH6T** - 860010067307 **SSH3T** - 860010067352	**Case Dimensions:**	**SSH6T** - 24"L x 14"W x 10"H **SSH3T** - 18"L x 12"W x 10"H
Unit Dimensions:	**SSH6T** - 8"H x 3-3/4"W x 2-3/4"D **SSH3T** - 5-3/4"H x 3"W x 2"D	**Case Weight:**	**SSH6T** - 29.5 lbs. **SSH3T** - 17.2 lbs.
Unit Weight:	**SSH6T** - 1 lb. 13 oz. **SSH3T** - 1 lb. 5.2 oz.	**Quantity per Case:**	10

SoftStart Home™ is a trademark of NetworkRV LLC dba SoftStart, Florida USA