

HEF-T-FOOT™

PRODUCT

HEF-T-FOOT™

APPLICATION

HVAC/R condensing units, heat pumps, piping, cabling, and other outdoor equipment

PURPOSE

Support equipment and enable pipework and cables to run underneath

FEATURES

- UV resistant molded recycled rubber
- Vibration / shock isolation / noise reduction
- Heavily textured non-skid surface
- Base mounting flange suitable for drilling and anchoring
- Spirit level

HEF-T-FOOT™ with Strut

- Aluminum strut channel molded in
- Strut external dimensions 0.81" x 1.55"
- Strut fits standard strut channel hardware and accessories

HEF-T-FOOT™ Universal (w/ Nut Inserts)

- 1.62" W x 1.0" H Rubber molded channel
- M10x20mm nut inserts molded into rubber channel

HEF-T-FOOT™ Installation Kits

- Aluminum strut molded in
- 4x Sliding Stud, Washer, Nut, M10x20mm x L1.6" (40mm) stud, zinc plated steel

MATERIALS

Rubber – Compression molded - Working temperature range 14°F to 167°F

Strut – 1.55" x 0.81" aluminum extrusion (fits standard strut components)

Inserts – M10 (metric course thread) x 20mm, zinc plated steel, through inserts

SPECIFICATIONS

HEF-T-FOOT™ with Steel Strut

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-250-S	HEF-T-FOOT™ 10" w/Strut	9.8"	6.3"	3.5"	6.2 lbs	350 lbs
FF-450-S	HEF-T-FOOT™ 18" w/Strut	17.7"	6.3"	3.5"	10.4 lbs	400 lbs
FF-600-S	HEF-T-FOOT™ 24" w/Strut	23.6"	6.3"	3.5"	16.8 lbs	440 lbs
FF-1000-S	HEF-T-FOOT™ 39" w/Strut	39.4"	6.3"	3.5"	26.5 lbs	485 lbs

HEF-T-FOOT™ Universal (w/Nut Inserts)

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-250-UNI	HEF-T-FOOT™ 10" w/Nut Inserts	9.8"	6.3"	3.5"	6.2 lbs	350 lbs

HEF-T-FOOT™ Installation Kits

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-450-S-KIT	1 Pair of FF-450-S + Installation Hardware	17.7"	6.3"	3.5"	20.8 lbs	800 lbs
FF-600-S-KIT	1 Pair of FF-600-S + Installation Hardware	23.6"	6.3"	3.5"	33.6 lbs	880 lbs
FF-1000-S-KIT	1 Pair of FF-1000-S + Installation Hardware	39.4"	6.3"	3.5"	53.0 lbs	970 lbs
FF-450N-S-KIT	1 Pair of narrow 450 HEF-T-FOOT + Installation Hardware	17.7"	4.3"	3.5"	17.0 lbs	550 lbs
FF-600N-S-KIT	1 Pair of narrow 600 HEF-T-FOOT + Installation Hardware	23.6"	4.3"	3.5"	28.0 lbs	600 lbs



FF-250-S

FF-450-S

FF-600-S

FF-1000-S



FF-600-S-KIT

FF-600N-S-KIT



HDK-HEFTFOOT

Installation Hardware

(Available as replacement hardware or for general use)