





VIEW W - W
SCALE 2:1


㉑ MODEL NUMBER
ZPS60K5E-PFV/TF5/TFD/TFE
ZPS35K6E-PFV
ZPS40K6E-PFV/TF5/TFD/TFE
ZPS42K6E-PFV
ZPS49K6E-PFV/TF5/TFD/TFE
ZPS51K6E-PFV/TF5/TFD/TFE
ZPS60K6E-PFV/TF5/TFD/TFE
ZPS52LXE-PFV
ZPS60LXE-TF5/TFD/TFE
㉓ ZPS61LXE-TFD


SPECIFICATIONS	
ES NO.	DESCRIPTION
ES92-155	CONVERSION-METRIC


NOTES:


1. ALL TOLERANCES ± 1.5 [0.06] UNLESS OTHERWISE SPECIFIED.
2. THE SUCTION TUBE, DISCHARGE TUBE, AND CIRCLE FENCE RADIAL DIMENSIONS ARE TO BE GAUGED FROM THE CENTER OF THE MOUNTING HOLE PATTERN.
3. TUBE ENDS MUST BE PLUGGED.
4. MOUNTING KIT.


GROMMET DUROMETER	4 FOOT KIT
35-45	527-0116-00











DETAIL Y
SCALE 2:1

ENG NOTICE NO.	REV.NO.	REVISIONS	DATE	BY	CHKD
ECN331681	23	ADDED ZPS61LXE-TFD MODEL	05-28-25	MA	BD
ECN330224	22	PICTORIAL UPDATE	01-21-25	CMA	DJS
ECN329379	21	ADDED MODELS	11-26-24	RAD	MA
ECN002005	0	RELEASED	01-27-11	DLK	EC

CONFIDENTIALITY NOTICE
THIS DRAWING AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF COPELAND LP AND/OR ITS AFFILIATES (COLLECTIVELY "COPELAND") AND SHALL BE RETURNED UPON DEMAND AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, DISCLOSED TO ANYONE ELSE OR USED, WITHOUT THE WRITTEN CONSENT OF COPELAND.

COPELAND

INTERPRET PER ASME Y14.5M-1994 AND COPELAND DESIGN STANDARDS DS2002

DO NOT SCALE DRAWING

◆ CRITICAL PRODUCT CHARACTERISTICS

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE MILLIMETER OR [INCH]
TOLERANCES:
1-PLACE : ±
2-PLACE : ± .
ANGULAR : ± 1

MATERIAL SPECIFICATION	DRAWN BY	SUPERSEDES DWG NO / REV NO
N/A	TM	497-1059-00 / 017
	DATE: 03-12-20	SCALE: 1:2
		DATE FORMAT: MM-DD-YY

TITLE: REF DWG-WELD COMP ASSM

DRAWING NUMBER: 497-1059-00 | SHEET 1 OF 1 | DWG: 4 | SIZE

©COPYRIGHT COPELAND - CONFIDENTIAL