Job: _____

Location: _____

Submitted to: _____

Submittal Prepared by: _____

Approve Date: _____

Date: _____

Series 55

SL And EA CRD

Specifications

UL Classification:
UL Classified UL 555C - For use in non-combustible installations rated 3 hours or less

Profile:
22Ga 1 Piece Rollformed Frame And Blades

Material:
Galvanized Steel

Fusible Link:
165° F Rated Link - Standard
212° F Rated Link - Optional

Fusible Link Type:
Standard Link Attachment (SL) - On 4" Diameter And Up
Easy Access Attachment (EA) - On 5" Diameter And Up

Sizes:
55SL Available in Sizes From 4"Ø to 24"Ø
55EA Available in Sizes From 5"Ø to 24"Ø

Thermal Blanket:
Ceramic Thermal Blanket Provided On Units With CRD Blade Areas Of Greater Than 84 Sq. In.





55 SL



55 EA

This product meets the requirements for ceiling dampers established by:

UL Standard 555C
NFPA Standard 90A
ICC Building Codes

3226-1650:0103

Part Number Format

5	5	E	A	0	8	G

MODEL

55 SERIES - CRD, ROUND, 3 HOUR

METHOD OF LINK ATTACHMENT

EA - EASY ACCESS LINK
SL - STANDARD LINK

DAMPER DIAMETER

MATERIAL & LINK TEMP.

G - GALVANIZED, W/165° LINK
H - GALVANIZED W/212° LINK

Qty.	Damper Diameter	Fusible Link Temp (165°F) std.