# CUT LEVEL 5
# NITRILE DIPPED GLOVES

# MORE DURABLE.
# BETTER PROTECTION.

EN388
CE
4X43E

## CUT LEVEL 5

**ANSI/ISEA 105**

A5
5 4

| EN388 STANDARDS | | | | | | |
|---|---|---|---|---|---|---|
| Abrasion | 1 | 2 | 3 | **4** | – | – |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | **X*** |
| Tearing | 1 | 2 | 3 | **4** | – | – |
| Puncture | 1 | 2 | **3** | 4 | – | – |
| Cut Resistance (TDM Test) | A | B | C | D | **E** | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**SMARTSWIPE™ Touch Screen Compatible Fingertips & Palms**

**High Dexterity Fingertips**



**Sandy Nitrile Grip**

**Light & Breathable Back**

**Color-Coded Bands**
Easy cut level identification

## SPECIFICATIONS

| | |
|---|---|
| **Gauge** | 13 |
| **Liner Material** | Nylon and HPPE Blend Knit |
| **Dip Material** | Sandy Nitrile |
| **Cuff Style** | Elasticated Knit |

## RECOMMENDED APPLICATIONS

- Duct Work
- Cutting
- High Dexterity Applications
- Oily & Wet Conditions
- Abrasive / Sharp Materials
- Glass & Metal Handling

## CARE INSTRUCTIONS

Machine wash warm water (105°F), mild detergent, no bleach.
Line dry.

| SIZE | 1 PAIR | 12 PAIR (Contractor Pack) |
|---|---|---|
| S | 48-73-8650 | 48-73-8650E |
| M | 48-73-8651 | 48-73-8651E |
| L | 48-73-8652 | 48-73-8652E |
| XL | 48-73-8653 | 48-73-8653E |
| XXL | 48-73-8654 | 48-73-8654E |

**SEE MORE PPE**

or visit https://qr.mke.tl/2d235


Milwaukee®