

## SEALING COMPOUND

- Hot or cold applications
- Flexible at -20°F and non-sagging up to 350°F
- Self adhesive and easy to apply
- Non-staining and non-hardening
- Water and vapor proof with no odor - white in color
- Non corrosive to metals
- Seal duct work and other HVACR jobs
- Plug holes, cracks, and small voids
- For indoor and/or outdoor use

### Description

This compound is formulated and manufactured for use in many sealing, insulating, and general maintenance applications. It has excellent adhesion capability and is non-staining, non-hardening, and unaffected by wide variations in temperature. Thumb-Tite is packaged in 2 lb. boxes, each box contains two one pound bars. Sealing Cords are available in 3/8" pre-shaped extruded cords, with serrated release paper.

### Application

#### For Refrigeration:

- Seal out air and moisture
- Seal around tube entries
- Seal under latch plates
- Seal under hinges
- Seal over screw head

#### For Air Conditioning:

- Seal window openings
- Seal air ducts
- Seal adaptors and extensions
- Seal air, dust and moisture

### Thumb-Tite Directions for Use

Can be easily worked by hand into any desired shape. Simply press into place. Adheres to most clean, dry surfaces, including metal, wood, glass, masonry, plastic and rubber.

## Insulation Products

### Thumb-Tite™ and Sealing Cords



### Sealing Cords Directions for Use

- Cords are arranged between paper so that one cord at a time may be uncoiled or the entire group unrolled.
- No tools are required, press cords in place with thumb or forefinger - no mess, no smear.
- Openings must be clean, free of moisture, grease or loose particles. Adheres to any clean, dry surface.

### Thumb-Tite Packaging

2 lb. box **4216-92**

### Sealing Cords Packaging

3/8" x 25' Roll **4216-27**

