SAFETY DATA SHEET

DP 1010 GRAY, SMOOTH WATER BASED DUCT SEALANT

Page: 1

=======================================	======================================	
PRODUCT NAME: PRODUCT CODE:	GRAY, SMOOTH WATER BASED DUCT SEALANT DP 1010	
MANUFACTURERS' NAM	IE: DESIGN POLYMERICS	HMIS
ADDRESS:	3301 W. Segerstrom Ave. Santa Ana, CA 92704	Health Hazard1Fire Hazard0Reactivity0Personal ProtectionB
EMERGENCY PHONE: BUSINESS HOURS: CONTRACT NUMBER: REVISION DATE: INFORMATION PHONE: REVISION #: PREPARED BY: DOT HAZARD CLASS: SHIPPING NAME:	Chem-Tel: (800) 255-3924 (24 Hrs) 7:30am – 4:30pm PT MIS0005056 March 7, 2019 (714) 432-0600 14.2 Technical Dept. Supersedes all previous Not Hazardous UN Number N/A N/A Packing Group N/A	CLAMMARILITY 1 HRALTH REACTIVITY PROTECTIVE EQUIPMENT

		VAPOR PRESSURE	WEIGHT
REPORTABLE COMPONENTS	CAS NUMBER	mm Hg @ TEMP	PERCENT

None

CAS #	Trade secret Y/N	Chemical Name	Comment
Proprietary Blend	YES		

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Contact physician or emergency medical facility immediately.

SKIN: Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water for at least 15 minutes. Do not rub affected area. If irritation persists, get medical attention. Skin reaction may take 24 to 48 hours to develop. Wash contaminated clothing before reuse.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes while frequently lifting the upper and lower eyelids. If irritation persists, call a physician.

INGESTION: Do not induce vomiting. Contact physician or emergency medical facility immediately. Never give anything by mouth to an unconscious person.

	SECTION V - FIRE-FIGHTING MEASURES	
FLASH POINT: Not Applicable	METHOD USED: Not Ap	plicable

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A

METHOD USED: Not Applicable UPPER: N/A

EXTINGUISHING MEDIA: The product will only burn after the water it contains is driven off. For dried film use water, foam, carbon dioxide or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: When dried film burns, carbon dioxide (CO₂), carbon monoxide (CO), hydrogen chloride gas (HCl), and smoke are produced. Firefighters should wear self-contained breathing apparatus, especially in enclosed areas. Cool containers and minimize vapors with water spray.

SAFETY DATA SHEET

DP 1010 GRAY, SMOOTH WATER BASED DUCT SEALANT

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high temperatures may explode or burst due to build-up of steam pressure.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike, contain, or absorb with inert absorbent material. Collect spilled material in a salvage container. Prevent spill from entering sewers, drains, streams, waterways, or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **DO NOT ALLOW TO FREEZE.** Store in a cool dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. Avoid inhalation of excess vapors, ingestion, and unnecessary, prolonged, or repeated contact with this and any other chemical. Change soiled work clothes frequently. Clean hands after handling. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: Not required under normal conditions. Provide sufficient ventilation to maintain constant fresh air in workspace. If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

SKIN PROTECTION (PROTECTIVE GLOVES): Wear resistant gloves such as polyethylene.

EYE PROTECTION: Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious clothing. Eye wash station.

WORK / HYGENIC PRACTICES: Source of clean water should be available for flushing eyes and washing skin. Wash thoroughly after handling any chemicals, especially before eating, drinking, or smoking. Remove and launder contaminated clothing before reuse.

PHYSICAL FORM: Viscous liquid ODOR: Mild, sweet SOLUBILITY IN WATER: Miscible BOILING POINT: 212°F FREEZING POINT: 32° F (0° C) COATING V.O.C.: 0 g/l COLOR: Gray pH: 7.5-9.0 SPECIFIC GRAVITY (H₂O=1): 1.3-1.5 % VOLATILES BY WEIGHT: 25-35 VISCOSITY (cps): approx. 300,000-400,000

STABILITY: Stable at ambient temperatures.

CONDITIONS TO AVOID: Coagulation may occur after freezing, thawing, or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts, mineral acids (i.e. sulfuric, phosphoric, etc.) Strong oxidizing agents. Strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials on thermal decomposition including Carbon monoxide (CO), Carbon dioxide (CO₂), and various hydrocarbons. Under fire conditions, this product will release hydrogen chloride gas.

SAFETY DATA SHEET

DP 1010 GRAY, SMOOTH WATER BASED DUCT SEALANT

Page: 3

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EYES: In direct contact, may cause irritation. SKIN: Prolonged and repeated contact with product may cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE: May cause irritation to skin and eyes, gastrointestinal irritation, nausea, and vomiting. CHRONIC: Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

Ecotoxicity: No ecotoxicity date was found for the product Environmental Fate: No environmental information found for this product

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines

	======	SECTION XIV – TRANSPO	ORT INFORMATION	========	
DOT Hazard Class Shipping Name	Not Hazaro N/A	lous		lumber ing Group	N/A N/A

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Not listed as a hazardous substance

Section 313 Information (40 CFR 372) – Toxic Chemicals List: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

Component None Listed CAS#

% by Weight

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): None listed.

===============	======================================	=======================================
MSDS Creation Date:	January 24, 2017	
MSDS Revision Date:	March 7, 2019	
MSDS Revision Notes:	Update volatiles by weight	
MSDS Author:	Technical Department	

Disclaimer: The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.