



6230 All-Weather Roof Cement Asphalt Cement For Roofs

- Use in wet or dry conditions
- Seals cracks and splits on worn roofs

DESCRIPTION: Black Jack® All-Weather Roof Cement is an asphalt based roof patch designed to repair cracks, seams and holes in roofing materials. It seals damaged areas and gives a layer of waterproof protection. Dries black.

USES: On roofs around skylights, vents, exhaust pipes, chimneys, valleys, and in the repair of roof surfaces.

PREPARATION: Surfaces must be clean and free of surface rust and loose material. Apply when surface temperatures are between 50 °F and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70 °F to 80 °F) at least 24 hours prior to application to promote ease of application. Product is formulated to be used year round.

APPLICATION: Apply generously with a trowel or putty knife. It is highly recommended to reinforce the repair with a strip of universal patching fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. Allow product to cure a minimum of 30 - 60 days prior to application of reflective coating.

COVERAGE RATE: One gallon covers approximately 12 sq. ft. when applied 1/8" thick.

PRECAUTIONS: Apply in exterior applications only. Protective clothing, gloves and eyewear should be used during application of these products. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not use in drinking water or food systems. Protect from freezing. DO NOT HEAT OR THIN. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers.

CLEAN-UP: Clean tools or spills with mineral spirits.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 3 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6230-9-14	1 qt.	4.3" x 4.3" x 4.9"	29 fl.oz. / 858 mL	2.7 lbs.	6/case	027134623042
6230-9-34	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	9 lbs.	6/case	027134623011
6230-9-30	5 gal.	12" x 12" x 14.75"	4.75 gal. / 18 L	48 lbs.	1 ea.	027134623059

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101