

Low-VOC Spray-Can Travel-Tack

Installation Adhesive in a Portable Spray Can



PART NUMBER

308599 1 case with 12 12-oz spray cans

TECHNICAL DATA

Color	White
Consistency	Aerosol spray
Spray Pattern	Variable web
Odor	Mint when wet
Base	Polymer
Solvent	Acetone Blend
Initial Bonding Time	Immediate
Dry Time	2 minutes
Adhesion	Excellent
Service Temperature	120°F max
Surface Burning	Flame spread 0. Smoke developed 10. When tested in accordance with ASTM E84.
Water Resistance	Excellent
Mildew Resistance	Good
VOC	<54 g/l
Packaging	12-oz Spray cans
Flammability	Flammable when wet Non-flammable when dry

SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
VOC Limitation	SCAQMD Rule 1168	Pass
	Ozone Transport Commission (OTC)	Pass
	City of Los Angeles Approved RR #8069	Pass

Low-VOC Travel-Tack is a self-contained, instant-tacking portable spray system engineered to deliver a Low-VOC compliant adhesive with a web spray pattern. Travel-Tack's portability, limited equipment clean-up, and low equipment cost make this adhesive ideal for shop or field use.

APPLICATION

Temperature	60°F to 90°F (15.5°C to 32.2°C) (Keep at 70°F for optimum performance. If spray can temperature falls below 70°F, move it to a warm area until optimum performance is achieved.)
Method	Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil, moisture and grease.
Clean Up	UN-TACK Cleaner/Adhesive Remover, petroleum solvents or mineral spirits

STORAGE

Temperature	60°F to 95°F (15°C to 35°C)
Shelf Life	One year (unopened)

PRECAUTIONS

- Do not expose to heat or store above 100°F.
- Do not puncture or incinerate.
- Empty cans are not re-fillable. When empty, dispose by following local code requirements.
- Review Material Safety Data Sheet for safety information prior to use.

For Industrial Professional Use Only.