
777

General Purpose Electrical Tape



Backing: PVC Film

Adhesive: Rubber

Liner: N/A

Colors: Black

Specifications: UL 510 Classified

Standard Sizes: 3/4" x 60Ft

Applications

- Wire splicing
- Wire insulation
- Spiral wrapping electrical wire and harnesses

Features	Benefits
• PVC Backing	• Stretchy and conformable for wrapping wires • Durable • Conformable
• Rubber Adhesive	• Provides a strong long-term bond • No flagging or lifting
• UL 510 Classified	• Meets requirements for most electrical applications

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	20 oz/in	2.19 N/cm	PSTC-101
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-1000
Elongation	200%		
Dielectric Strength	600V		
Operating Temperature	40 - 180 °F	4 - 82 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.berryglobal.com
9/26/17