
POLYKEN®

243

Multi-Purpose Duct Tape



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Black

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- General repair
- General purpose construction uses
- Bundling, patching, and mending
- Seaming and hanging polyethylene sheeting
- Emergency tape for automotive applications

Features	Benefits
• PE-Coated Cloth Backing	• Conforms well to irregular surfaces • Resists twisting and curling
• Natural rubber based adhesive	• High adhesion and holding power for both rough and smooth surfaces
• Low VOC Content	• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10.0 mils	0.254 mm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Adhesion to Backing	43 oz/in	4.70 N/cm	PSTC-101
Tensile Strength	24 lb/in	42.03 N/cm	ASTM D-1000
Elongation	21%		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

Berry

25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.berryglobal.com
12/11/17