


Premium UL 181A-P & 181B-FX Listed Foil Tape



Backing: Printed 2.1 mil Aluminum Foil

Adhesive: Cold weather Acrylic

Liner: Polycoated Natural Kraft Liner

Colors: Aluminum

Specifications: UL 181A-P & UL 181B-FX Listed

Standard Sizes: 2.5" x 60Yd, 72mm x 55m

Applications

- Permanently seals seams in fiberglass duct board and flexible ducts for HVAC systems
- Suitable for use on rigid sheet metal ducts
- Durable seal for dryer ventilation

Features

Benefits

- | | |
|--|--|
| • Aggressive cold weather acrylic adhesive | • Superior performance in all climate conditions |
| • Kraft Release Liner | • Low odor |
| • UL 181A-P & 181B-FX Listed | • Mold and mildew resistant |
| | • Reduced environmental impact |
| | • Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED® |
| • Low VOC Content | • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED® |

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/o Liner	4.8 mils	0.122 mm	ASTM D-1000
Foil Thickness	2.1 mils	0.053 mm	ASTM D-1000
Adhesion to Steel	68 oz/in	7.44 N/cm	PSTC-101
Adhesion to Backing	60 oz/in	6.56 N/cm	PSTC-101
Tensile Strength	28 lb/in	49.04 N/cm	ASTM D-1000
Application Temperature	-10 to 200 °F	4 to 93 °C	
Operating Temperature	-25 to 325 °F	-32 to 163 °C	
Flame Spread	3		
Smoke Developed	0		
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway, Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge, it is true and