




BioMAX™ 99.97% & 99.99% 2000 CFM Series

FEATURES:

- Individually Tested High Capacity Media
- Particle Board & Galvanized Steel Cell Sides

DESCRIPTION: HEPA grade filter with high capacity media.

APPLICATIONS: Air handlers in medical facilities, pharmaceuticals, clean room manufacturing and indoor gun ranges.

EFFICIENCY: 99.97% at 0.3μ or 99.99% at 0.3μ

MEDIA: Submicron glass fibers formed into a water-resistant, high efficiency high density, wet-laid paper mat.

RECOMMENDED FINAL PRESSURE DROP: Consult factory. Rule of thumb is change filter when the initial pressure drop doubles.

TEMPERATURE: Maximum continuous operating temperature 180°F (82°C)

RATINGS: UL Rated

PRICE PAGE: L1-3

See Bulletin No. K-603A for more details

Actual Size W x H x D	Koch Part #	Airflow Capacity (CFM)	Initial Resistance (inches W.G.)	Media Area (sq. ft.)	Efficiency	Shipping Weight (lbs)
Style SBW - Particle Board Cell Sides						
24x24x11.50	H66G2X1	2000	1.5	282	99.97 @ 0.3 Micron	43
24x12x11.50	H62G2X1	1000	1.5	140	99.97 @ 0.3 Micron	38
23.38x23.38x11.50	H64G2X1	1900	1.5	275	99.97 @ 0.3 Micron	38
23.38x11.38x11.50	H60G2X1	950	1.5	132	99.97 @ 0.3 Micron	43
Style SBM - Galvanized Steel Cell Sides						
24x24x11.50	H66A2X1	2000	1.5	282	99.97 @ 0.3 Micron	45
24x12x11.50	H62A2X1	1000	1.5	140	99.97 @ 0.3 Micron	40
23.38x23.38x11.50	H64A2X1	1900	1.5	275	99.97 @ 0.3 Micron	40
23.38x11.38x11.50	H60A2X1	950	1.5	132	99.97 @ 0.3 Micron	45
Style SBW - Particle Board Cell Sides						
24x24x11.50	H66G4X1	2000	1.5	282	99.99 @ 0.3 Micron	43
24x12x11.50	H62G4X1	1000	1.5	140	99.99 @ 0.3 Micron	38
23.38x23.38x11.50	H64G4X1	1900	1.5	275	99.99 @ 0.3 Micron	38
23.38x11.38x11.50	H60G4X1	950	1.5	132	99.99 @ 0.3 Micron	43
Style SBM - Galvanized Steel Cell Sides						
24x24x11.50	H66A4X1	2000	1.5	282	99.99 @ 0.3 Micron	45
24x12x11.50	H62A4X1	1000	1.5	140	99.99 @ 0.3 Micron	40
23.38x23.38x11.50	H64A4X1	1900	1.5	275	99.99 @ 0.3 Micron	40
23.38x11.38x11.50	H60A4X1	950	1.5	132	99.99 @ 0.3 Micron	45

Notes:

- All BioMAX HEPA HC filters are furnished with one gasket on the downstream side. If additional gaskets are needed, state location when ordering.
- Contact factory for sizes not listed above. A customer drawing or written submittal is required on all special sizes.
- BioMAX HEPA HC Style SBM for High Temperature applications are available.