

High Wall Heat Pump Ductless System

Indoor Model: 40MHHQ24---3

Submittal Data

Job Data:

Location:

Buyer: Buyer P.O. #:

Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Anti-corrosive fin coating

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

*For residential applications. See warranty for full details.

System	Size		24
	Indoor Model		40MHHQ24---3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Powered from outdoor unit	
	MCA	A.	0.45
Controls	Wireless Remote Controller (°F/°C Convertible)		Standard
	Wired Remote Controller (°F/°C Convertible)		Optional
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	63~90 (17~32)
	Heating Indoor DB Min -Max	° F (° C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area (sq. ft.)	Sq. Ft.	2.58
	No. Rows		2
	Fins per inch		20
	Circuits		2
Indoor	Unit Width	in (mm)	43.83 (1113)
	Unit Height	in (mm)	13.41 (341)
	Unit Depth	in (mm)	9.22 (234)
	Net Weight	lbs (kg)	40.12(18.2)
	Number of Fan Speeds		4
	Airflow (lowest to highest)	CFM	353/483/589/647
	Sound Pressure (lowest to highest)	dB(A)	38/42/48/49
	Air throw Data	ft (m)	37.7 (11.5)
	Moisture removal	Pint/h (L/h)	5.73 (2.71)
	Field Drain Pipe Size O.D.	in (mm)	0.625 (16)

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0401AAA	Wired Remote Control 7 Day Programmable

Compatibility Table

Indoor Unit	40MHHQ24---3
Outdoor Unit	38MHRQ24A--3

Construction View

Indoor Model: 40MHHQ24---3

