

PART NUMBER 042007DB


Non-UL Listed Single Pair Shielded Low-Cap Non-Plenum Direct Burial Cable

DIRECT BURIAL

SUNLIGHT RESISTANT

24 AWG SHIELDED

LOW CAP 12.5pF



CABLE SPECIFICATIONS

| | |
|---------------------------|--|
| DESCRIPTION | 1 Pair, 24 AWG Tinned Copper Shielded RS-232, RS-422, RS-485 Low-Capacitance Communication, Instrumentation and Special Application Direct Burial Non-UL Cable |
| CONDUCTOR | 24 AWG (7/32) Tinned Copper |
| INSULATION | Foam Polyethylene .016" |
| COLOR CODE | Black/White |
| SHIELD | Aluminum Mylar |
| DRAIN WIRE | 24 AWG Stranded Tinned Copper |
| JACKET | Black PE .020" |
| JACKET COLOR | Black Jacket |
| MARKING | LO-CAP 12.5 Pf/FT DIRECT BURIAL 24 AWG 1 PAIR SHIELDED |
| OVERALL DIAMETER | .156" Nom. |
| CABLE WEIGHT | 16 Lbs/Mft. |
| CAPACITANCE | 12.5 pF/Ft. Nom. |
| IMPEDANCE | 100 Ohms/Mft. |
| TEMPERATURE RATING | 75 C / 300 Volts Max. |

INDUSTRY STANDARDS

AGENCY APPROVALS None



All specifications referenced are nominal measurements unless otherwise noted.