

# ZP44K5E-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	44500	60000
Power (W):	4220	2770
Current (Amps):	12.15	8.9
EER(BTU/Wh):	10.55	21.6
Mass Flow (lbs/hr):	656	737
Sound Data @ 45 / 130		
Sound Power (dBA):	71 Avg	76 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-03-01	
Mechanical		
Displacement (in^3/Rev):	2.56	
Displacement (ft^3/Hr):		
Overall Length (in):	9.56	
Overall Width (in):	9.56	
Overall Height (in):	16.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

<b>Mounting Height (in):</b>	17.17
<b>Suction Size (in),Type:</b>	7 / 8 Stub
<b>Discharge Size (in),Type:</b>	1 / 2 Stub
<b>Initial Oil Charge (oz):</b>	42
<b>Oil Recharge (oz):</b>	36
<b>Net Weight (lbs):</b>	68.2
<b>Internal Free Volume (in^3):</b>	209.5

#### Horse Power:

\*Overall compressor height on Copeland Brand Product's specified mounting grommets.

#### Electrical

<b>LRA High* (Amps):</b>	98.0
<b>LRA Low*(Amps):</b>	
<b>LRA Half Winding (Amps):</b>	
<b>MCC (Amps):</b>	22.6
<b>Max Operating Current (Amps):</b>	20.0
<b>RLA, MCC/1.4(use for contactor selection)(Amps):</b>	16.1
<b>RLA, MCC/1.56(use for breaker &amp; wire size selection)(Amps):</b>	14.5
<b>RPM:</b>	3500
<b>Box IP :</b>	21
<b>UL File No:</b>	SA-2337
<b>UL File Date:</b>	2003-12-17

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

#### Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

#### Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	Air Conditioning

### Service Parts

Reference	Component	Quantity	Description	Comment
1	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
1	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
2	527-0116-00	1	SPACER-MOUNTING ASSM	
7	998-0510-98	1	VLV KIT 1/2"SWT/1-14UNC	DISCHARGE ROTALOCK
8	998-0510-90	1	VLV KIT 7/8"SWT / 11/4-12UNC	SUCTION ROTALOCK
9	998-7026-00	1	HEATER JUNCTION BOX KIT	
99	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	998-0034-02	1	SERV ADAPTOR KIT 7/8 STUB	SWEAT TO ROTALOCK ADAPTER KIT SUCTION
99	998-0034-08	1	ADPTR 11/4-12 TO 7/8 ID	ROTALOCK TO SWEAT ADAPTER KIT SUCTION
99	998-0034-15	1	SERV ADAPTOR KIT 1/2 STUB	SWEAT TO ROTALOCK ADAPTER KIT DISCHARGE

### Accessories

### Accessories

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322017- E20ENN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017- R54BDB	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke, With Bypass, Frame H3X
(1) Variable Frequency Drive	EVH-322017- R21BDB	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke, With Bypass, Frame H2S
(1) Variable Frequency Drive	EVH-322017- R54BDN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017- R21BEN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017- R21BDN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017- R54BEN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke + EMI Filter, No Options, Frame 2

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322017-E20EFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-N20MFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Basic, IP20, With add on EMI filter, No Options, Frame 2

### Electrical Components

Electrical Components	
Part No: 071-0501-53	
Usage Description: Internal Protector	
<u>Vendor Part Number</u>	
34HM402	
<u>Vendor Name</u>	
T.I.	
Part No: 071-0501-73	<b>Stator</b>
Usage Description: Internal Protector	Part No: 546-2090-14
<u>Vendor Part Number</u>	Usage Description: Stator
34HM409	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 0.87
T. I.	Run Wdg: 0.00
<b>Stator</b>	
Part No: 546-2115-02	
Usage Description: Stator	
Resistance: +/-7%	
Start Wdg: 1.06	
Run Wdg: 0.00	

### Nomenclature

ZP44K5E-TF5
<b>Family Series</b>
<b>Z:</b> Scroll
<b>Application Range</b>
<b>P:</b> A/C - R-410A/B
<b>Capacity</b>
<b>44K:</b> Capacity Multiplier-1000

**Oil Type****E:** Polyol Ester**Motor Type****T:** 3 Phase**Motor Protection****F:** Internal Inherent Protection**Voltage****5:** 60Hz (200/230-3) 50Hz (200/220-3)

## Miscellaneous

## Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
<a href="#">HFC R-410A</a>	50	3 Ø	200/220 V	R1 AC

## Nomenclature

[ZP44K5E-TF5](#)

Date	Data Group	Field	Old Data	New Data
12-Jan-2009	Status	Status	P	A
09-Jan-2009	Rating	PubCode		Y
16-Nov-2007	Rating	PubCode		PRE
15-Aug-2009	Mech	CFH		311.476264
15-Aug-2009	Mech	Cu In Per Rev		2.563
15-Aug-2009	Mech	Init Oil Charge		42
15-Aug-2009	Mech	Rech Oil Charge		38
14-Jan-2009	Elec	MCC	21.1	22.6
14-Jan-2009	Elec	RLA	15.1	16.1
21-Sep-2008	Elec	Hi LRA	NA	98.0