

ZPS35K5E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	115
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	100
Capacity (BTU/hr)	36800	45400
Power (W):	3500	2870
Current (Amps):	15.5	12.75
EER(BTU/Wh):	10.5	15.8
Mass Flow (lbs/hr):	538	602
Sound Data @		
Sound Power (dBA):	72 Avg	77 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-04-24	
Mechanical		
Displacement (in^3/Rev):	2.14	
Displacement (ft^3/Hr):	260.4	
Overall Length (in):	9.56	
Overall Width (in):	9.56	
Overall Height (in):	16.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	17.17
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	42
Oil Recharge (oz):	36
Net Weight (lbs):	72.9
Internal Free Volume (in^3):	186.8

Horse Power:

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	96.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	28
Max Operating Current (Amps):	27.0
RLA, MCC/1.4(use for contactor selection)(Amps):	20.0
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	17.9
RPM:	3500
Box IP :	21
UL File No:	SA2337
UL File Date:	2003-12-17

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-25	45.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	208/230	1	60	A/C, 67% Load Of Compressor Model

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
2	914-0036-03	1	CAP START KIT	
3	940-0001-79	1	RELAY-POTENTIAL KIT	
4	527-0116-00	1	SPACER-MOUNTING ASSM	
5	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
5	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
5	918-0041-02	1	HEATER-CRANKCASE	480V 40W WRAP AROUND
6	529-0060-24	1	POWER CABLE-MOLDED PLUG	3-PIN MOLDED PLUG
6	529-0138-01	1	CABLE-POWER ASSM	2-PIN MODULATION PLUG
99	914-0037-36	1	RUN CAP KIT	
99	998-0069-01	1	ADAPTER & SEAL KIT	

Accessories

Accessories		
Category	Part Number	Description
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
Crankcase Heaters	018-0096-06	Crankcase Heater, 240V, 40W, 31.75" Lead Length
Crankcase Heaters	018-0096-05	Crankcase Heater, 480V, 40W, 48.25" Lead Length
Crankcase Heaters	018-0096-04	Crankcase Heater, 240V, 40W, 48.25" Lead Length

Category	Part Number	Description
Crankcase Heaters	018-0096-03	Crankcase Heater, 575V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-02	Crankcase Heater, 480V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-00	Crankcase Heater, 240V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
Crankcase	018-0096-01	Crankcase Heater, 120V, 40W, 21.75" Lead Length

Electrical Components

Electrical Components	
Part No: 071-0546-03	Stator
Usage Description: Internal Protector	Part No: 546-5011-05
<u>Vendor Part Number</u>	Usage Description: Stator
15HM1413	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 1.55
T.I.	Run Wdg: 0.62
Potential	Start Capacitor
Part No: 040-0166-37	Part No: 014-0061-27
Usage Description: Potential Relay	Low MFD: 88.0
<u>Vendor Part Number</u>	Type:Start Capacitor
RVA2AE6D-946	High MFD: 106.0
<u>Vendor Name</u>	Usage Description: Start Capacitor
ELECTRICA	Volts: 330
Run Capacitor	
Part No: 014-0064-25	
Low MFD: 45.0	
Type:Run Capacitor	
High MFD: 0.0	
Usage Description: Run Capacitor	
Volts: 370	

Nomenclature

ZPS35K5E-PFV

Family Series

Z: Scroll

Application Range

P: A/C - R-410A/B

Modulation

S: Two Step

Capacity

35K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	60	1 Ø	208/230 V	R1 A6

Nomenclature

[ZPS35K5E-PFV](#)

Date	Data Group	Field	Old Data	New Data
17-Mar-2011	Status	Status	P	A
17-Mar-2011	Status	Status	P	A
01-Mar-2013	RatingRefNo	RatingRefNo	11-19	13-143
01-Mar-2013	RatingRefNo	RatingRefNo	11-20	13-144
26-Feb-2013	Rating	PubCode		Y
11-Jan-2011	Rating	PubCode		PRE
27-May-2016	2 Pt Perf	Amp Cond 1	12.75	15.5
27-May-2016	2 Pt Perf	Amp Cond 2	15.5	12.75
27-May-2016	2 Pt Perf	Cap Cond 1	45400	36800

Date	Data Group	Field	Old Data	New Data
------	------------	-------	----------	----------