ZR25K5E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Mounting Width (in):

7.50

		Performance	9	
Evaporator Temp. (°F)			45	50
Condensing Temp. (°F)			130	100
Return Gas Temp. (°F)			65	70
Liquid Temp. (°F)			115	85
Capacity (BTU/hr)			24300	32800
Power (W):			2360	1535
Current (Amps):			10.4	6.65
EER(BTU/Wh):			10.3	21.35
Mass Flow (lbs/hr):			354	404
Sound Data @				
Sound Power (dBA):			68 Avg	73 Max
Vibration mils(peak-peak):			2.0 Avg	3.0 Max
Record Date:			2010-11-16	
		Mechanical		
Displacement (in^3/Rev):	2.08			
Displacement (ft^3/Hr):				
Overall Length (in):	9.50			
Overall Width (in):	9.50			
Overall Height (in):	15.86			
Mounting Length (in):	7.50			

Mounting Height (in):	16.08
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	25
Oil Recharge (oz):	19
Net Weight (lbs):	50.1
Internal Free Volume (in^3):	118

Horse Power:

 ${}^*\text{Overall compressor height on Copeland Brand Product's } \textbf{\textit{specifical}} \textbf{\textit{mounting grommets}}.$

LRA High* (Amps):	68.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	21
Max Operating Current (Amps):	14.0
RLA, MCC/1.4(use for contactor selection)(Amps):	15.0
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	13.5
RPM:	3500
Box IP:	21
UL File No:	SA-2337

UL File Date:

Capacitors

Туре	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-08	40.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
		Alternate App	lications		

Refrigerant	Voltage	Phase	Frequency	Application

No data available in table

^{*}Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	918-0052-00	1	CRANKCASE HEATER KIT	240V 40W WRAP AROUND
1	918-0052-01	1	CRANKCASE HEATER KIT	120V 40W WRAP AROUND
2	527-0044-15	1	SPACER - MOUNTING ASSM	
13	914-0037-12	1	RUN CAP KIT W/CLAMP	
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	

Accessories

Accessories				
Category	Part Number	Description		
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W		
Crankcase Heaters	018-0094-01	Crankcase Heater, 120V, 40W		
Crankcase Heaters	018-0094-03	Crankcase Heater, 480V, 40W, 21.25" Lead Length		
Crankcase Heaters	018-0094-04	Crankcase Heater, 575V, 40W, 21.25" Lead Length		
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W		
Crankcase Heaters	018-0094-01	Crankcase Heater, 120V, 40W		
Crankcase Heaters	018-0094-04	Crankcase Heater, 575V, 40W, 21.25" Lead Length		

Electrical Components

Electrical Components

Part No: 071-0512-37

Usage Description: Internal Protector

Vendor Part Number

15HM2344

Vendor Name

SENSATA

Potential

Part No: 040-0166-37

Usage Description: Potential Relay

Vendor Part Number

RVA2AE6D-946

Vendor Name

ELECTRICA

Run Capacitor

Part No: 014-0064-08

Low MFD: 40.0

Type:Run Capacitor

High MFD: 0.0

Usage Description: Run Capacitor

Volts: 370

Stator

Part No: 546-5016-09

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.70

Run Wdg: 1.02

Start Capacitor

Part No: 014-0061-27

Low MFD: 88.0

Type:Start Capacitor

High MFD: 106.0

Usage Description: Start Capacitor

Volts: 330

Nomenclature

ZR25K5E-PFV

Family Series

Z: Scroll

Application Range

R: A/C - R-22/407C/134a

Capacity

25K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	60	1 Ø	208/230 V	R1
		Nomenclatu	re	
		ZR25K5E-PF	V	
Date	Data Group	Field	Old Data	New Data
12-May-2010	Rating	PubCode	PRE	Υ
29-Mar-2010	Rating	PubCode		PRE
13-Jun-2010	Mech	CFH	355.71245	6 252.656712
13-Jun-2010	Mech	Cu In Per Rev	2.927	2.079
13-Jun-2010	Mech	Init Oil Charge	42	25
13-Jun-2010	Mech	Mech Spec No	MS91-Z14	30 MS91-Z1403
13-Jun-2010	Mech	Rech Oil Charge	38	19
17-Nov-2010	2 Pt Perf	Amp Cond 1	6.65	10.4
17-Nov-2010	2 Pt Perf	Amp Cond 2	10.4	6.65
17-Nov-2010	2 Pt Perf	Cap Cond 1	32800	24300