ZR44K5E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

		Performance	9	
Evaporator Temp. (°F)			45	50
Condensing Temp. (°F)			130	100
Return Gas Temp. (°F)			65	70
Liquid Temp. (°F)			115	85
Capacity (BTU/hr)			42200	56500
Power (W):			4000	2640
Current (Amps):			17.75	12.45
EER(BTU/Wh):			10.55	21.4
Mass Flow (lbs/hr):			614	696
Sound Data @ 45 / 130				
Sound Power (dBA):			70 Avg	75 Max
Vibration mils(peak-peak):			2.0 Avg	3.0 Max
Record Date:			2015-10-13	
		Mechanical		
Displacement (in^3/Rev):	3.56			
Displacement (ft^3/Hr):				
Overall Length (in):	9.69			
Overall Width (in):	9.69			
Overall Height (in):	16.94			
Mounting Length (in):	7.50			
Mounting Width (in):	7.50			

Mounting Height (in):	17.17
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	42
Oil Recharge (oz):	34
Net Weight (lbs):	68.1
Internal Free Volume (in^3):	191.1

Horse Power:

 ${}^*\text{Overall compressor height on Copeland Brand Product's } \textbf{\textit{specifical}} \textbf{\textit{mounting grommets}}.$

LRA High* (Amps):	137.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	31.5
Max Operating Current (Amps):	29.0
RLA, MCC/1.4(use for contactor selection)(Amps):	22.5
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	20.2
RPM:	3500
Box IP:	21
UL File No:	SA-2337

UL File Date:

Capacitors

Туре	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
Start Capacitor	014-0064-26	60.0	0.0	370	

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application

No data available in table

^{*}Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
1	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
2	527-0116-00	1	SPACER-MOUNTING ASSM	
4	914-0037-37	1	RUN CAP KIT	
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	

Accessories

Accessories				
Category	Part Number	Description		
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length		
Crankcase Heaters	018-0096-04	Crankcase Heater, 240V, 40W, 48.25" Lead Length		
Crankcase Heaters	018-0096-03	Crankcase Heater, 575V, 40W, 21.75" Lead Length		
Crankcase Heaters	018-0096-02	Crankcase Heater, 480V, 40W, 21.75" Lead Length		
Crankcase Heaters	018-0096-01	Crankcase Heater, 120V, 40W, 21.75" Lead Length		
Crankcase Heaters	018-0096-00	Crankcase Heater, 240V, 40W, 21.75" Lead Length		
Crankcase Heaters	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length		
Crankcase Heaters	018-0096-05	Crankcase Heater, 480V, 40W, 48.25" Lead Length		
Crankcase Heaters	018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length		
Crankcase Heaters	018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length		

Electrical Components

Electrical Components

Part No: 071-0546-05

Usage Description: Internal Protector

Vendor Part Number

Part No: 546-5010-18

Stator

Usage Description: Stator

15HM1646

Vendor Name

T.I.

Potential

Part No: 040-0166-37

Usage Description: Potential Relay

Vendor Part Number

RVA2AE6D-946

Vendor Name

ELECTRICA

Start Capacitor

Part No: 014-0064-26

Low MFD: 60.0

Type:Start Capacitor

High MFD: 0.0

Usage Description: Start Capacitor

Volts: 370

Resistance: +/-7%

Start Wdg: 1.29 Run Wdg: 0.49

Start Capacitor

Part No: 014-0061-27

Low MFD: 88.0

Type:Start Capacitor

High MFD: 106.0

Usage Description: Start Capacitor

Volts: 330

Nomenclature

ZR44K5E-PFV

Family Series

Z: Scroll

Application Range

R: A/C - R-22/407C/134a

Capacity

44K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)

Miscellaneous

Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	60	1 Ø	208/230 V	R1
		Nomenclatu ZR44K5E-P		
Date	Data Group	Field	Old Data	New Data
30-Apr-2013	Rating	PubCode		Υ