

# ZR44K5E-TF5

HFC, R-407C, 60 Hz, 3 - Phase, 200/230 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

**Production Status:** This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

## Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	42200	57000
Power (W):	3920	2540
Current (Amps):	11.25	8.4
EER(BTU/Wh):	10.75	22.4
Mass Flow (lbs/hr):	614	701
Sound Data @ 45 / 130		
Sound Power (dBA):	73 Avg	78 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2015-10-13	
Mechanical		
Displacement (in^3/Rev):	3.56	
Displacement (ft^3/Hr):		
Overall Length (in):	9.69	
Overall Width (in):	9.69	
Overall Height (in):	16.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

<b>Mounting Height (in):</b>	17.17
<b>Suction Size (in),Type:</b>	7 / 8 Stub
<b>Discharge Size (in),Type:</b>	1 / 2 Stub
<b>Initial Oil Charge (oz):</b>	42
<b>Oil Recharge (oz):</b>	34
<b>Net Weight (lbs):</b>	63.8
<b>Internal Free Volume (in^3):</b>	211.3

**Horse Power:**

\*Overall compressor height on Copeland Brand Product's specified mounting grommets.

<b>LRA High* (Amps):</b>	98.0
<b>LRA Low*(Amps):</b>	
<b>LRA Half Winding (Amps):</b>	
<b>MCC (Amps):</b>	20
<b>Max Operating Current (Amps):</b>	17.0
<b>RLA, MCC/1.4(use for contactor selection)(Amps):</b>	14.3
<b>RLA, MCC/1.56(use for breaker &amp; wire size selection)(Amps):</b>	12.8
<b>RPM:</b>	3500
<b>Box IP :</b>	21
<b>UL File No:</b>	SA-2337

**UL File Date:**

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Capacitors**

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

**Alternate Applications**

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	200/220	3	50	Air Conditioning

### Service Parts

Reference	Component	Quantity	Description	Comment
1	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
1	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
2	527-0116-00	1	SPACER-MOUNTING ASSM	
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	

### Accessories

#### Accessories

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322017-E20ENN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R54BDB	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke, With Bypass, Frame H3X
(1) Variable Frequency Drive	EVH-322017-R21BDB	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke, With Bypass, Frame H2S
(1) Variable Frequency Drive	EVH-322017-R54BDN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R21BEN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R21BDN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R54BEN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-E20EFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-N20MFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Basic, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-N20MNN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Basic, IP20, Standard, No Options, Frame 2

### Electrical Components

#### Electrical Components

Part No: 071-0501-53	<b>Stator</b>
Usage Description: Internal Protector	Part No: 546-2090-14
<u>Vendor Part Number</u>	Usage Description: Stator
34HM402	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 0.87
T.I.	Run Wdg: 0.00

## Nomenclature

ZR44K5E-TF5
<b>Family Series</b>
<b>Z:</b> Scroll
<b>Application Range</b>
<b>R:</b> A/C - R-22/407C/134a
<b>Capacity</b>
<b>44K:</b> Capacity Multiplier-1000
<b>Oil Type</b>
<b>E:</b> Polyol Ester
<b>Motor Type</b>
<b>T:</b> 3 Phase
<b>Motor Protection</b>
<b>F:</b> Internal Inherent Protection
<b>Voltage</b>
<b>5:</b> 60Hz (200/230-3) 50Hz (200/220-3)

## Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
<a href="#">HCFC R-22</a>	50	3 Ø	200/220 V	R1
<a href="#">HCFC R-22</a>	60	3 Ø	200/230 V	R1
<a href="#">HFC R-407C</a>	50	3 Ø	200/220 V	R1 AC
Nomenclature				
<a href="#">ZR44K5E-TF5</a>				
Date	Data Group	Field	Old Data	New Data
13-Oct-2015	Rating	PubCode		O

Date	Data Group	Field	Old Data	New Data
------	------------	-------	----------	----------