

ZR72KCE-TF5

HCFC, R-22, 60 Hz, 3 - Phase, 200/230 V [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	73500	86000
Power (W):	6250	4460
Current (Amps):	18.1	14.2
EER(BTU/Wh):	11.7	19.3
Mass Flow (lbs/hr):	1080	1110
Sound Data @		
Sound Power (dBA):	75 Avg	80 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	
Mechanical		
Displacement (in^3/Rev):	5.98	
Displacement (ft^3/Hr):		
Overall Length (in):	9.69	
Overall Width (in):	9.69	
Overall Height (in):	17.75	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	18.00
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	60
Oil Recharge (oz):	56
Net Weight (lbs):	85.0
Internal Free Volume (in^3):	248
Horse Power:	6.0

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	156
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	29
Max Operating Current (Amps):	26.0
RLA, MCC/1.4(use for contactor selection)(Amps):	20.7
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	18.6
RPM:	3500
Box IP :	21
UL File No:	SA-2337
UL File Date:	1993-07-26

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	200/220	3	50	Air Conditioning
R-134a HFC	200/230	3	60	Air Conditioning
R-22 HCFC	200/220	3	50	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	918-0043-00	1	HEATER-CRANKCASE	240V 70W WRAP AROUND
1	918-0043-01	1	HEATER-CRANKCASE	480V 70W WRAP AROUND
2	527-0116-00	1	SPACER-MOUNTING ASSM	

Accessories

Accessories		
Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322025-E20ENN	EVM, 3Ø, 200-240v, Output 200-240v@25A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322025-R21BDB	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP21, With 5% DC Link Choke, With Bypass, Frame H2S
(1) Variable Frequency Drive	EVH-322025-R54BEN	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP54, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322025-R54BDN	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322025-R21BEN	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322025-R21BDN	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322025-R54BDB	EVH, 3Ø, 200-240v, Output 200-240v@25A, LCD Keypad, IP54, With 5% DC Link Choke, With Bypass, Frame H3X
(1) Variable Frequency Drive	EVM-322025-E20EFN	EVM, 3Ø, 200-240v, Output 200-240v@25A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322025-N20MFN	EVM, 3Ø, 200-240v, Output 200-240v@25A, Basic, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322025-N20MNN	EVM, 3Ø, 200-240v, Output 200-240v@25A, Basic, IP20, Standard, No Options, Frame 2

Electrical Components

Electrical Components	
Part No: 071-0519-20	
Usage Description: Internal Protector	
<u>Vendor Part Number</u>	
35HM150	
<u>Vendor Name</u>	
T. I.	
Part No: 071-0679-09	Stator
Usage Description: Internal Protector	Part No: 546-2093-59
<u>Vendor Part Number</u>	Usage Description: Stator
35HM422	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 0.56
SENSATA	Run Wdg: 0.00
Stator	
Part No: 546-2122-09	
Usage Description: Stator	
Resistance: +/-7%	
Start Wdg: 0.55	
Run Wdg: 0.00	

Nomenclature

ZR72KCE-TF5

Family Series

Z: Scroll

Application Range

R: A/C - R-22/407C/134a

Capacity

72K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

T: 3 Phase

Motor Protection

F: Internal Inherent Protection

Voltage

5: 60Hz (200/230-3) 50Hz (200/220-3)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	50	3 Ø	200/220 V	R1 AC
HFC R-134a	50	3 Ø	200/220 V	R1 AC
HFC R-134a	60	3 Ø	200/230 V	R1 AC
HFC R-407C	50	3 Ø	200/220 V	R1 AC
HFC R-407C	60	3 Ø	200/230 V	R1 AC
Nomenclature				
ZR72KCE-TF5				
Date	Data Group	Field	Old Data	New Data
06-Mar-2014	2 Pt Perf	Amp Cond 1	18.2	18.1