

ZP182KCE-TFD

HFC, R-410A, 60 Hz, 3 - Phase, 460 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	105
Capacity (BTU/hr)	183000	163000
Power (W):	16300	14400
Current (Amps):	26.3	24.1
EER(BTU/Wh):	11.2	11.3
Mass Flow (lbs/hr):	2690	2270
Sound Data @		
Sound Power (dBA):	82 Avg	87 Max
Vibration mils(peak-peak):	3.0 Avg	4.5 Max
Record Date:	2017-03-22	
Mechanical		
Displacement (in^3/Rev):	10.20	
Displacement (ft^3/Hr):		
Overall Length (in):	10.38	
Overall Width (in):	11.23	
Overall Height (in):	21.72	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	23.03
Suction Size (in),Type:	1 3 / 8 Stub
Discharge Size (in),Type:	7 / 8 Stub
Initial Oil Charge (oz):	110
Oil Recharge (oz):	106
Net Weight (lbs):	146.0
Internal Free Volume (in^3):	856
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	179.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	41
Max Operating Current (Amps):	34.0
RLA, MCC/1.4(use for contactor selection)(Amps):	29.3
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	26.3
RPM:	3500
Box IP :	21
UL File No:	SA-2337
UL File Date:	1996-09-27

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	380/420	3	50	Air Conditioning

Service Parts

Reference	Component	Quantity	Description	Comment
1	918-0047-00	1	HEATER-CRANKCASE	120V 90W WRAP AROUND
1	918-0047-01	1	HEATER-CRANKCASE	240V 90W WRAP AROUND
1	918-0047-02	1	HEATER-CRANKCASE	480V, 90W, WRAP AROUND
2	527-0210-00	1	MOUNTING SPACER ASSM	
9	998-0510-90	1	VLV KIT 7/8"SWT / 11/4-12UNC	DISCHARGE
11	998-0010-00	1	SIGHTGLASS KIT	
14	998-0034-02	1	SERV ADAPTOR KIT 7/8 STUB	DISCHARGE SWEAT TO ROTALOCK
14	998-0034-04	1	ADAP KIT 13/8"SWT / 13/4 RL	SUCTION SWEAT TO ROTALOCK
14	998-0034-08	1	ADPTR 11/4-12 TO 7/8 ID	DISCHARGE ROTALOCK TO SWEAT
14	998-0034-13	1	ADPTR 13/4-12 TO 13/8 ID	SUCTION ROTALOCK TO SWEAT

Accessories

Accessories

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-344031-E20ENN	EVM, 3Ø, 380-480v, Output 380-480v@31A, Pro, IP20, Standard, No Options, Frame 3
(1) Variable Frequency Drive	EVM-344031-N20MNN	EVM, 3Ø, 380-480v, Output 380-480v@31A, Basic, IP20, Standard, No Options, Frame 3
(1) Variable Frequency Drive	EVM-344031-N20MFN	EVM, 3Ø, 380-480v, Output 380-480v@31A, Basic, IP20, With add on EMI filter, No Options, Frame 3
(1) Variable Frequency Drive	EVM-344031-E20EFN	EVM, 3Ø, 380-480v, Output 380-480v@31A, Pro, IP20, With add on EMI filter, No Options, Frame 3
(1) Variable Frequency Drive	EVH-344031-R21BDN	EVH, 3Ø, 380-480v, Output 380-480v@31A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-344031-R21BEN	EVH, 3Ø, 380-480v, Output 380-480v@31A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 2

Category	Part Number	Description
(1) Variable Frequency Drive	EVH-344031-R54BDN	EVH, 3Ø, 380-480v, Output 380-480v@31A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-344031-R54BEN	EVH, 3Ø, 380-480v, Output 380-480v@31A, LCD Keypad, IP54, With 5% DC Link Choke + EMI Filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-344031-R21BDB	EVH, 3Ø, 380-480v, Output 380-480v@31A, LCD Keypad, IP21, With 5% DC Link Choke, With Bypass, Frame H2S

Electrical Components

Electrical Components	
Part No: 071-0505-38	Stator
Usage Description: Internal Protector	Part No: 546-1200-04
<u>Vendor Part Number</u>	Usage Description: Stator
32HM1535	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 0.83
SENSATA	Run Wdg: 0.00
Stator	
Part No: 546-2200-00	
Usage Description: Stator	
Resistance: +/-7%	
Start Wdg: 0.83	
Run Wdg: 0.00	

Nomenclature

ZP182KCE-TFD
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Capacity
182K: Capacity Multiplier-1000
Oil Type
E: Polyol Ester

Motor Type**T:** 3 Phase**Motor Protection****F:** Internal Inherent Protection**Voltage****D:** 60Hz (460-3) 50Hz (380/420-3)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	50	3 Ø	380/420 V	R1 AC

Nomenclature

[ZP182KCE-TFD](#)

Date	Data Group	Field	Old Data	New Data
21-Mar-2007	Status	Status	P	A
13-Sep-2007	Sound	Sound Ave	82	80
13-Sep-2007	Sound	Sound Max	87	85
21-Mar-2007	Sound	Sound Ave	80	82
21-Mar-2007	Sound	Sound Max	85	87
21-Mar-2007	Sound	Sound Start	83	85
21-Mar-2007	Sound	Sound Start Max	91	93
21-Mar-2007	Sound	Sound Stop	77	82
21-Mar-2007	Sound	Sound Stop Max	84	90
12-Apr-2006	Sound	Vibration Ave	2.5	3