

CRNQ-050E-TFD

HCFC, R-22, 60 Hz, 3 - Phase, 380/460 V [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	61500	77000
Power (W):	6100	4850
Current (Amps):	8.9	7.5
EER(BTU/Wh):	10.1	15.9
Mass Flow (lbs/hr):	900	995
Sound Data @		
Sound Power (dBA):	80 Avg	85 Max
Vibration mils(peak-peak):	5.0 Avg	6.0 Max
Record Date:	2014-03-06	
Mechanical		
Displacement (in^3/Rev):	6.22	
Displacement (ft^3/Hr):		
Overall Length (in):	11.38	
Overall Width (in):	9.38	
Overall Height (in):	16.13	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	16.50
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	70
Oil Recharge (oz):	66
Net Weight (lbs):	82.0
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	65.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	13.5
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	9.6
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.7
RPM:	
Box IP :	
UL File No:	
UL File Date:	1984-12-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	380/420	3	50	Air Conditioning
R-22 HCFC	380/420	3	50	High Temp
R-22 HCFC	380/460	3	60	High Temp
R-404A HFC	380/420	3	50	High Temp

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	380/420	3	50	Air Conditioning

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	521-0191-00	1	TERMINAL-SCREW GROUP	
99	521-0192-00	1	TERMINAL KIT	
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	918-0088-05	1	HEATER-CRANKCASE KIT	45/65W 480V FLEXIBLE
99	921-0227-00	1	CONNECTOR BLOCK KIT	

Accessories

Accessories		
Category	Part Number	Description
(1) Variable Frequency Drive	EVH-344012-R54BDB	EVH, 3Ø, 380-480v, Output 380-480v@11A, LCD Keypad, IP54, With 5% DC Link Choke, With Bypass, Frame H3X

Electrical Components

Electrical Components	
<div> <div>Part No: 071-0501-55</div> <div>Usage Description: Internal Protector</div> <div>Vendor Part Number</div> <div>34HM513</div> <div>Vendor Name</div> <div>SENSATA</div> <div>Stator</div> <div>Part No: 546-5105-02</div> <div>Usage Description: Stator</div> </div>	<div> <div>Stator</div> <div>Part No: 546-5105-01</div> <div>Usage Description: Stator</div> <div>Resistance: +/-7%</div> <div>Start Wdg: 2.47</div> <div>Run Wdg: 0.00</div> </div>

Resistance: +/-7%

Start Wdg: 2.47

Run Wdg: 0.00

Nomenclature

CRNQ-050E-TFD

Family Series

C: CR Compressors

Application Range

R: R-22/ High Temp. A/C & Heat Pump

Capacity

: Capacity

Oil Type

: --

Motor Type

T: 3 Phase

Motor Protection

F: Internal Inherent Protection

Voltage

D: 60Hz (460-3) 50Hz (380/420-3)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	50	3 Ø	380/420 V	R1 AC
HCFC R-22	50	3 Ø	380/420 V	R1 HT
HCFC R-22	60	3 Ø	380/460 V	R1 HT
HFC R-404A	50	3 Ø	380/420 V	R1 HT
HFC R-407C	50	3 Ø	380/420 V	R1 AC
HFC R-407C	60	3 Ø	380/460 V	R1 AC

Nomenclature

[CRNQ-050E-TFD](#)

Date	Data Group	Field	Old Data	New Data
------	------------	-------	----------	----------

Date	Data Group	Field	Old Data	New Data
14-Jan-2014	Sound	Vibration Ave	2.4	5
14-Jan-2014	Sound	Vibration Max	3.4	6
06-Mar-2014	2 Pt Perf	Cap Cond 1	61300	61500